



# MJCF Gas Fryers -- Domestic & Export

Project \_\_\_\_\_  
 Item \_\_\_\_\_  
 Quantity \_\_\_\_\_  
 CSI Section 11400 \_\_\_\_\_  
 Approval \_\_\_\_\_  
 Date \_\_\_\_\_

MJCF Gas Fryers -- Domestic & Export

## Models

MJ1CF



Shown with optional analog controller and casters

## Standard Features

- Open-pot design is easy to clean
- 80-lb (40 liter) oil capacity
- 150,000 Btu/hr input (37,783 kcal) (44 kw)
- Frying area 18" x 19" x 4-1/2" (45.7 x 48.3 x 11.4 cm)
- Millivolt controller (outside the cabinet), no electric connection required
- Reliable, centerline, fast-action temperature probe
- Deep cold zone, 1-1/4 in. (3.2 cm) IPS ball-type drain valve
- Master Jet burners ensure even heat distribution
- Stainless steel frypot and door, enamel cabinet
- Two twin baskets
- 6" steel legs with 1" adjustment
- 3/4" gas connection

## Options & Accessories

- Analog or Digital controllers
- Piezo ignitor
- On/off toggle switch (millivolt controller only)
- Frypot cover
- Stand-alone spreader cabinet
- Casters
- Melt cycle (above controllers only)
- Full basket
- Triplet basket
- Chicken/Fish tray
- Sediment tray
- Splash shield

See Frymaster domestic price list for other available options and accessories

## Specifications

### Specifically designed for high production of chicken, fish and other breaded products


The MJ1CF has an 80-lb. (40 liter\*) oil capacity. The frying area is 18" x 19" x 4-1/2" (45.7 x 48.3 x 11.4 cm). This 150,000 Btu/hr. (37,783 kcal/hr.) (44 kw) model is specifically designed for high production of chicken, fish and other breaded products.

The exclusive 1° action thermostat anticipates rapid rate of temperature rise, reducing temperature overshoot, extending oil life and producing a more uniformly-cooked product. Centerline thermostat mounting permits quick sensing of cold food placed in either basket.

The open stainless steel frypot has a large heat transfer area to fry more product per load. The open-pot design can be cleaned and wiped down by hand.

The large cold zone and forward sloping bottom help collect and remove sediment from the frypot to safeguard oil quality and support routine frypot cleaning.

\*Liter conversions are for solid shortening @ 70°F.




8700 Line Avenue  
 Shreveport, LA 71106-6800  
 USA

Tel: 318-865-1711  
 Tel: 1-800-221-4583  
 Fax: 318-868-5987  
 E-mail: info@frymaster.com

www.frymaster.com  
 Bulletin No. 818-0467  
 Revised 6/16/15





**DIMENSIONS**

MODEL NO.	OIL CAPACITY	OVERALL SIZE (cm)			DRAIN HEIGHT	NET WEIGHT	SHIPPING INFORMATION					
		WIDTH	DEPTH	HEIGHT			WEIGHT	CLASS	CU. FT.	DIMENSIONS (cm)		
MJ1CF	80 lbs. (40 liters)	20-3/4" (53)	39-7/8" (101.2)	46-3/8" (117.7)	11-1/2" (29.2 cm)	250 lbs. (113 kg)	297 lbs. (135 kg)	85	31.96	<b>W</b> 25" (63.5)	<b>D</b> 47" (119.4)	<b>H</b> 47" (119.4)

**POWER REQUIREMENTS**

MODEL NO.	BASIC DOMESTIC/ EXPORT OPTIONS	
	CONTROLS/ FRYPOT	FILTER
MJ1CF	N/A (millivolt controller)	
Non-millivolt controllers	120V 1 A 220V 1 A	120V 8 A 220V 5 A

**NOTES**

- 1-1/2" (3.8 cm) kitchen main manifold gas supply line required. Gas inlet size (I.D.) should be no smaller than that provided for connection to the fryer(s). See service manual and/or plumbing codes for proper pipe sizing. Recommended minimum store manifold pressure to be 6" W.C. for natural gas and 11" W.C. for L.P. gas. Check plumbing codes for proper supply line sizing to attain burner manifold pressure of 3.5" W.C. natural or 8.25" W.C. L.P.

**• DO NOT CURB MOUNT**

**CLEARANCE INFORMATION**

- A minimum of 24" (61.0 cm) should be provided at the front of the unit for servicing and proper operation, 6" (15.2 cm) between the sides and rear of the fryer to any combustible material, and a minimum of 18" (45.7 cm) between the flue outlet and the lower edge of the exhaust hood filter.

**HOW TO SPECIFY**

The following descriptions will assist with ordering the features desired for this equipment:

- MJ1CF MJCF fryer with thermostat knob, millivolt controls
- SD Stainless steel frypot and door -- enamel cabinet
- SC Stainless steel frypot, door and cabinet
- SE Stainless steel pot, door, and cabinet ends