

STAINLESS STEEL EQUIPMENT FILLER TABLE

, i	TFMS Series w/ Open Base



OPEN BASE

Model	L	W	Wt.	Cu. Ft.
TFMS-182		24"	23 lbs.	2
TFMS-180	18"	30"	25 lbs.	3
TFMS-183		36"	32 lbs.	3
TFMS-152		24"	22 lbs.	2
TFMS-150	15"	30"	24 lbs.	3
TFMS-153		36"	31 lbs.	3
TFMS-122		24"	21 lbs.	2
TFMS-120	12"	30"	22 lbs.	3
TFMS-123		36"	29 lbs.	3

Item #:	_ Qty #:
Model #:	
Project #:	

FEATURES:

TOP is furnished with 1 5/8" sanitary rolled rim edge in front. Square edges on sides and 1/1/2" splash of single metal thickness on rear. Hat channels stud welded to top which reinforces and maintains a level working surface.

Welded Front to Back Leg Assembly.

Rear (Left to Right) Stretcher bolts to side leg assemblies.

Aluminum die cast "leg-to-shelf" clamp secures shelf to leg eliminating unsightly nuts and bolts. Undershelf is fully adjustable.

CONSTRUCTION:

All TIG welded. Exposed weld areas polished to match adjacent surfaces.

Entire top mechanically polished to a satin finish.

Top is sound deadened.

Roll formed embossed galvanized hat channels are secured to top by means of structural adhesive and weld studs. Gussets welded to support hat sections.

MATERIAL:

TOP: 16 gauge stainless steel type "304" series. SHELF: 16 gauge stainless steel type "304" series. STRETCHERS: 1 5/8" diameter tubular stainless steel.

LEGS: 1 5/8" diameter tubular stainless steel. LEGS: 1 5/8" diameter tubular stainless steel.

Stainless steel gussets.

1" stainless steel bullet feet.

Model W Cu. Ft. L Wt. **TFMSU-182** 24" 29 lbs. 2 18" **TFMSU-180** 30" 2 33 lbs. 24" 2 TFMSU-152 24 lbs. 15" TFMSU-150 30" 29 lbs. 2



Customer Service Available To Assist You 1-800-645-3166 8:30 am - 8:00 pm E.S.T.

For Orders & Customer Service: Email: customer@advancetabco.com or Fax: 631-242-6900 For Smart Fabrication[™] Quotes: Email: smartfab@advancetabco.com or Fax: 631-586-2933

W/ ADJ. UNDERSHELF

DIMENSIONS and SPECIFICATIONS

TOL ± .500"

ALL DIMENSIONS ARE TYPICAL



