

STAINLESS STEEL

DEMO TABLE & CEILING MOUNTED DEMO MIRROR



DEMO TABLE

MODEL #	Table Size W x L	Mirror Size	Wt.	Cu.
VSS-DT-365	36" x 60"	24" x 48"	275 lbs.	18
VSS-DT-366	36" x 72"	24" x 60"	305 lbs.	23



CEILING MOUNTED MIRROR

MODEL #	Mirror Size W x L	Wt.	CU.
MI-48	24" x 48"	91 lbs.	7
MI-60	24" x 60"	115 lbs.	8

 Item #: ______ Qty #: _____

 Model #: ______

 Project #: ______

FEATURES:

Fully adjustable glass mirror tilts to desired position.

Locking Knob for securing mirror's position.

Glass Mirror

DEMO TABLE:

Top is furnished with a 2" x 1" square die embossed NO-DRIP countertop edge with a 1/2" return on 4 sides.

Pre-engineered welded angle adapters insure ease of future drawer installation.

36" wide table supplied with THREE hat channels stud welded to reinforce and maintain a level working surface.

Aluminum die cast "leg-to-shelf" clamp secures shelf to leg eliminating unsightly nuts and bolts. Undershelf is adjustable.

CEILING MOUNTED MIRROR:

Tubular stainless steel mounting support.

CONSTRUCTION:

All TIG welded. Exposed weld areas polished to match adjacent surfaces.

Entire top mechanically polished to a satin finish. Countertop edge polished to a MIRROR finish (Demo Table Only).

Top is sound deadened.

Roll formed embossed galvanized hat channels are secured to top by means of structural adhesive and weld studs (Demo Table Only).

Gussets welded to support hat sections (Demo Table Only).

MECHANICAL:

Mirror tilts to desired position.

MATERIAL:

Square tubular mirror frame is 16 ga., 304 type Stainless steel.

Glass Mirror

DEMO TABLE:

TOP: 14 gauge type "304" stainless steel. **SHELF**: 18 gauge type "304" stainless steel.

LEGS: Legs are 1 5/8" diameter tubular, 16 gauge stainless steel '304'

type series. 1" adjustable stainless steel bullet feet.

CEILING MOUNTED MIRROR:

1 5/8" diameter 4' tubular, 16 gauge type "304" stainless steel posts.

16 gauge (tubular) support uprights.

PRINT REQUIRED - SPECIFY POST LENGTH



Customer Service Available To Assist You 1-800-645-3166 8:30 am - 8:00 pm E.S.T.

Email Orders To: customer@advancetabco.com. For Smart Fabrication™ Quotes, Email To: smartfab@advancetabco.com or Fax To: 631-586-2933

NEW YORK Fax: (631) 242-6900 **GEORGIA** Fax: (770) 775-5625

TEXAS Fax: (972) 932-4795

NEVADA

Fax: (775) 972-1578

DETAILS and SPECIFICATIONS

TOL ± .500" ALL DIMENSIONS ARE TYPICAL



