



# Hot Well Exposed Element Steam Tables

Models  ST 120V/240V  PST 120/240V

PRODUCT:

QUANTITY:

## Designed Smart

### Compact Design with High Output

APW Hot Well Exposed Element Steam Tables are all stainless steel wrapper.

Features include:

- Individual controls for peak performance.
- High-output tubular heating elements.
- UL and UL Sanitation approved
- Adaptable for wet applications



## APW Wyott Design Features

- Stainless steel wrapper
- Recessed controls for improved protection and safety
- Full range of options and accessories

## Reliability backed by APW Wyott's Warranty

All APW Wyott cooking equipment is backed by a 1-year limited warranty and a 1-year on-site labor warrant. \*

- Certified by the following agencies:



See reverse side for product specifications.



APW Wyott Foodservice Equipment Company \* 729 Third Ave., Dallas, TX 75226  
(800) 527-2100 \* (214)421-7366 \* Fax (214) 565-0976 \* [www.apwwyott.com](http://www.apwwyott.com) \* [info@apwwyott.com](mailto:info@apwwyott.com)

Rev.02/15/11

KaTom Restaurant Supply, Inc.



2:15 AMP 125V



# Hot Well Exposed Element Steam Tables

Models □ ST 120V/240V □ PST 120/240V

PRODUCT:

QUANTITY:

ITEM:

## PRODUCT SPECIFICATIONS

### Stationary

Non-Marking feet adjust unit height from 34 1/2" to 35 1/2".

### Construction:

All Stainless Steel wrapper. Individual controls for peak performance.

Freight Class: 85 verify

FOB: Standex Dock

Also available in 208V. When Ordering replace the 240 with 208. Example: ST-208-3

Model #	# of top openings	Length	Weight	Electrical data
ST-120-2	2	30 5/8"	97 lbs	1000W, 120V,
ST-240-2	2	30 5/8"	97 lbs	1500W, 240V,
ST-120-3	3	44 5/8"	125 lbs	1500W, 120V,
ST-240-3	3	44 5/8"	125 lbs	2250W, 240V,
ST-120-4	4	58 5/8"	158 lbs	2000W, 120V,
ST-240-4	4	58 5/8"	158 lbs	3000W, 240V,
ST-120-5	5	72 5/8"	193 lbs	2500W, 120V,
ST-240-5	5	72 5/8"	193 lbs	3750W, 240V,

Model in the chart indicate units with galvanized legs and aluminized under shelf. To order units with stainless steel legs and under shelf insert an S after the well number. Example ST-120-3S

### Portable






Push handle and 4" – diameter casters, two with brake included

Model #	# of top openings	Length	Weight	Electrical data
PST-120-2	2	30 5/8"	101 lbs	1000W, 120V,
PST-240-2	2	30 5/8"	101 lbs	1500W, 240V,
PST-120-3	3	44 5/8"	129 lbs	1500W, 120V,
PST-240-3	3	44 5/8"	129 lbs	2250W, 240V,
PST-120-4	4	58 5/8"	162 lbs	2000W, 120V,
PST-240-4	4	58 5/8"	162 lbs	3000W, 240V,
PST-120-5	5	72 5/8"	199 lbs	2500W, 120V,
PST-240-5	5	72 5/8"	199 lbs	3750W, 240V,

Model in the chart indicate units with galvanized legs and aluminized under shelf. To order units with stainless steel legs and under shelf insert an S after the well number. Example PST-120-3S

Also available in 208V. When Ordering replace the 240 with 208. Example: PST-208-3

### Receptacle configurations required for Sealed Well Food Tables.

 15 AMP 125V	 15 AMP 250V	 20 AMP 250V	 30 AMP 250V	 30 AMP 125V
Model# ST-120-2	Model # ST-240-2	Model # ST-240-4	Model # ST-240-4	Model # ST-240-5
ST-120-3	ST-240-3			
furnished with NEMA 5-15 plug	furnished with NEMA 6-15 plug	furnished with NEMA 66-20 plug	furnished with NEMA 6-30 plug	furnished with NEMA 5-30 plug

\*APW Wyott reserves the right to modify specifications or discontinue models without incurring obligation.



APW Wyott Foodservice Equipment Company \* 729 Third Ave., Dallas, TX 75226  
(800) 527-2100 \* (214)421-7366 \* Fax (214) 565-0976 \* [www.apwwyott.com](http://www.apwwyott.com) \* info@apwwyott.com

Rev.02/15/11

KaTom Restaurant Supply, Inc.