

Stationary Models ST-2 ST-2S ST-3 ST-3S ST-4 ST-4S ST-5 ST-5S
 Portable Models PST-2 PST-2S PST-3 PST-3S PST-4 PST-4S PST-5 PST-5S
 QUANTITY: ITEM:

PRODUCT:

Designed Smart

APW Hot Well Sealed Exposed Element Steam Tables constructed of stainless steel with die stamped top.

- Individual infinite switch heat controls; thermostatic also available
- Indicator light remains on while control is in ON position
- Standard with 500 watt elements; 750 watt elements also available
- Stainless steel liner is standard
- Each compartment insulated with 1" thick fiberglass
- ½" thick poly cutting board mounted on stainless steel shelf supported by stainless steel brackets
- Available with either, stainless steel legs and under shelf or coated steel legs and under shelf
- Cord and plug included with standard units



Model: ST-5

APW Wyott Design Features

Heavy gauge stainless steel construction for the body.

Features include:

- Poly cutting board
- Stainless steel undershelf & legs
- High-output tubular heating elements.
- Stationary and portable units available.
- UL and UL Sanitation approved
- Full range of options and accessories.
- Individual controls for peak performance
- Recessed controls for improved protection and safety

Reliability Backed by APW Wyott's Warranty

All APW Wyott cooking equipment is backed by a 1-year limited warranty and a 1-year on-site labor warrant. *

Certified by the following agencies:



Options and Accessories

Cutting Boards

- NSF approved Plastic Cutting Boards – 7 1/2" X 12"
- Hardwood – 8" X 1-1/4"
- Richlite Heat-Resistant – 8" X 12"

- Stainless Steel Dish Shelf
- Serving Shelves with Glass Protector
- Plate Shelves
- Tubular Tray Slide – 3-Bar
- Buffet Shelves
- Spillage Pans
- Adjustable Overall Shelf System
- Deluxe Serving Shelves
- Solid Tray Slide
- Roll top Covers
- Adapter Bars for Food Pans – 10" X 12"
- Adapter Tops for Round Inserts – 4-, 7-, and 11-Quart

Stationary Models ST-2 ST-2S ST-3 ST-3S ST-4 ST-4S ST-5 ST-5S
 Portable Models PST-2 PST-2S PST-3 PST-3S PST-4 PST-4S PST-5 PST-5S

PRODUCT SPECIFICATIONS

Construction:

All stainless steel wrapper. Individual controls for peak performance.

Freight Class: 100

FOB: Allen, TX 75013

Stationary


Non-Marking feet adjust unit height from 34 1/2" to 35 1/2".

Dimensions						
Model	# of top openings	Length	Width	Height	Weight	Electrical Data
ST-120-2 or 2S	2	30 1/2"	22 3/4"	34"	150	1000W, 120V, 8.33A
ST-208-2 or 2S	2	30 1/2"	22 3/4"	34"	150	1500W, 208V, 7.21A
ST-240-2 or 2S	2	30 1/2"	22 3/4"	34"	150	1500W, 240V, 6.25A
ST-120-3 or 3S	3	44 1/2"	22 3/4"	34"	190	1500W, 120V, 12.5A
ST-208-3 or 3S	3	44 1/2"	22 3/4"	34"	190	2250W, 208V, 10.82A
ST-240-3 or 3S	3	44 1/2"	22 3/4"	34"	190	2250W, 240V, 9.38A
ST-120-4 or 4S	4	58 1/2"	22 3/4"	34"	225	2000W, 120V, 16.67A
ST-208-4 or 4S	4	58 1/2"	22 3/4"	34"	225	3000W, 208V, 14.42A
ST-240-4 or 4S	4	58 1/2"	22 3/4"	34"	225	3000W, 240V, 12.5A
ST-120-5 or 5S	5	72 1/2"	22 3/4"	34"	260	2500W, 120V, 20.83A
ST-208-5 or 5S	5	72 1/2"	22 3/4"	34"	260	3750W, 208V, 18.03A
ST-240-5 or 5S	5	72 1/2"	22 3/4"	34"	260	3750W, 240V, 15.63A

Portable

Push handle and 4" – diameter casters, two with brake included

Dimensions						
Model	# of top openings	Length	Width	Height	Weight	Electrical Data
PST-120-2 or 2S	2	30 1/2"	22 3/4"	34"	150	1000W, 120V, 8.33A
PST-208-2 or 2S	2	30 1/2"	22 3/4"	34"	150	1500W, 208V, 7.21A
PST-240-2 or 2S	2	30 1/2"	22 3/4"	34"	150	1500W, 240V, 6.25A
PST-120-3 or 3S	3	44 1/2"	22 3/4"	34"	190	1500W, 120V, 12.5A
PST-208-3 or 3S	3	44 1/2"	22 3/4"	34"	190	2250W, 208V, 10.82A
PST-240-3 or 3S	3	44 1/2"	22 3/4"	34"	190	2250W, 240V, 9.38A
PST-120-4 or 4S	4	58 1/2"	22 3/4"	34"	225	2000W, 120V, 16.67A
PST-208-4 or 4S	4	58 1/2"	22 3/4"	34"	225	3000W, 208V, 14.42A
PST-240-4 or 4S	4	58 1/2"	22 3/4"	34"	225	3000W, 240V, 12.5A
PST-120-5 or 5S	5	72 1/2"	22 3/4"	34"	260	2500W, 120V, 20.83A
PST-208-5 or 5S	5	72 1/2"	22 3/4"	34"	260	3750W, 208V, 18.03A
PST-240-5 or 5S	5	72 1/2"	22 3/4"	34"	260	3750W, 240V, 15.63A



furnished with NEMA 5-15 plug	furnished with NEMA 6-15 plug	furnished with NEMA 6-20 plug	furnished with NEMA 5-30 plug	furnished with NEMA 6-30 plug	furnished with NEMA 5-50 plug
-------------------------------	-------------------------------	-------------------------------	-------------------------------	-------------------------------	-------------------------------

*APW Wyott reserves the right to modify specifications or discontinue models without incurring obligation.