

12 Cup Digital Automatic Coffee Brewer with Pourover



Model CDBCFFP

(2 top warmers)

(decanters sold separately)

Dimensions: 20.9" H x 8.5" W x 17.8" D
(53.1cm H x 21.6cm W x 45.2cm D)

Features

Automatic CDBC Coffee Brewers

- Large 200 oz. (5.9 litres) tank provides back-to-back brewing capacity.
- Adjusts automatically to varying water pressure.
- Quicker install saves up to 30 minutes. Pot level, cold brew lock-out and tank temperature set easily from advanced touch pad on front of machine.
- Electronic diagnostics and built in tank drain make service easier.
- Ensures coffee brew quality with cold brew lock out capability.
- SplashGard® funnel deflects hot liquids away from the hand.
- Coffee extraction controlled with pre-infusion or pulse brew and digital temperature control.
- Pourover feature.

For current specification sheets and other information, go to www.bunn.com.

Related Products

Easy Clear® EQ-17-TL

Product No. : 30200.1000

Dimensions:

12⁷/₁₆" H x 2¹/₂" W x 3" D
31.6 cm H x 6.35 cm W x 7.62 cm D



Paper Filter Pack

Product No. : 20115.0000

Packed per case: 1,000

Dimensions: 4¹/₄" Base x 2³/₄" Sidewall
10.8 cm Base x 6.98 cm Sidewall



Easy Clear® ED-17-TL

Product No. : 30201.1001

Dimensions: 8¹/₄" H x 2⁵/₁₆" Dia.
20.95 cm H x 5.87 cm Dia.

Easy Pour® black decanter

Product No. : 06100.0101

Quantity: 1 (also packaged in quantities of 2, 3, 6, 12, & 24)



Easy Pour® orange decanter (for decaf)

Product No. : 06101.0101

Quantity: 1 (also packaged in quantities of 2, 3, 6, 12, & 24)



1GPR SS Portable Server on an RWS1 Warmer

1GPR Product No. : 12487.0001*

RWS1 Product No. : 12203.0010

*Also available with side handles or black decor.



Model

CDBCFFP15

Agency Listing



Dimensions & Specifications

Model	Product #	Volts	Amps	Tank Heater Watts	Total Watts	Brewing Capacity	Cu. Ft.	Shipping Weight	Cord Attached
CDBCFCP15 (2 top)	28800.0300	120	15	1425	1800	4.5 gal./hr.	4.3	32 lbs.	Yes
CDBCFCP15 (2 top)*	28800.0303	120	15	1425	1800	4.5 gal./hr.	4.3	33.5 lbs.	Yes
CDBCFP35*	28800.0304	120/240	17.5†	3500	3850	7.5 gal./hr.	4.0	30 lbs.	No
CDBCFCP35*	28800.0305	120/240	17.5†	3500	3850	7.5 gal./hr.	4.0	30 lbs.	No
CDBCFCP20*	28800.0309	120	17.9	1800	2150	5.1 gal./hr.	4.0	30 lbs.	No
CDBCFP35 (Hi-lime)*	28800.0307	120/240	15.9†	3500	3100	7.5 gal./hr.	4.3	30 lbs.	No
CDBCFCP35 (Hi-lime)*	28800.0308	120	15.9	1425	1800	4.5 gal./hr.	4.3	30 lbs.	Yes


*Stainless steel funnel. †Current at 120/240 Volts

Brewing capacity: based upon incoming water temp of 60°F (140°F rise) per 1/2 gallon brew time of 4 minutes.

Models listed as 120/208V or 120/240V must be connected to 208V or 240V electrical service respectively. Please refer to the installation manual.

Electrical: 120 volt, 15 amp. models require 2-wires plus ground service rated 120V, single phase, 60 Hz.

Plumbing: 20-90 psi (138-621 kPa). Machines supplied with 1/4" male flare fitting. Twin models supplied with 3/8" male flare fitting.



BUNN Corporation - 1400 Stevenson Drive Springfield, Illinois 62703 • 800-637-8606 • 217-529-6601 • Fax 217-529-6644 • www.bunn.com

BUNN® practices continuous product research and improvement. We reserve the right to change specifications and product design without notice. Such revisions do not entitle the buyer to corresponding changes, improvements, additions or replacements for previously purchased equipment.

All dimensions shown in inches. Bunn Corporation owns all copyrights relating to materials in this publication. Please contact Bunn Corporation to request permission to reproduce any portion of this publication.