

## Twin Tall Infusion Coffee Brewer

### Features



#### Infusion Coffee Brewer

- Brews up to 18.9 gallons (71.5 litres) of perfect coffee per hour.
- Large 5.6 gallon (21.2 litre) tank provides back-to-back brewing capacity
- Designed to brew into 1 gallon and 1.5 gallon (3.8 and 5.7 litre) ThermoFresh™ servers with base for easy transport of coffee to other locations.
- Three brew buttons allow for 3 separate brewing profiles. Two programmable batch switches allow full and half batch brewing.
- Easy Pulse interface allows automatic programming of pulse routine.
- BrewWISE® intelligence with pre-infusion and pulse brew for maximum flavor extraction. DBC grinder communicates with brewer through Smart Funnel®.
- Energy-saver mode reduces tank temperature during idle periods.
- Digital display in English/Spanish for easier programming and control. Advertising messages and machine status also displayed. Display capable of showing English or Metric measurements.
- Compatible with BUNNlink™.

#### Model ICB-Twin Tall with 1.5 Gal ThermoFresh® Server

(TF server sold separately)

Dimensions: 34.4"H x 22.6"W x 20.1"D  
(87.4cm H x 57.4cm W x 51.1cm D)

For current specification sheets and other information, go to [www.bunn.com](http://www.bunn.com).

### Related Products

**Easy Clear® EQHP-10**  
Product No. : 39000.0004



**1.5 gallon ThermoFresh Server**  
Product No.: 39550.0000

**1.5 gallon Digital ThermoFresh Server**  
Product No.: 39550.0050



**Easy Clear® EQHP-10L**  
Product No. : 39000.0001

**1 gallon ThermoFresh Server**  
Product No.: 39500.0000

**1 gallon Digital ThermoFresh Server**  
Product No.: 39500.0050

**Single/Dual Filter Pack**  
Product No. : 20138.0000

Packed per case: 500

Dimensions:

5¼" Base x 4¼" Sidewall

13.3 cm Base x 10.8 cm Sidewall



#### Model

ICB-Twin Tall

#### Agency Listing



E9001.0075A

Patents Apply

04/07

A3.5c


## Dimensions & Specifications

Model	Product #	Volts	Amps	Tank Heater Watts	Total Watts	Capacity	Cubic Measure	Shipping Weight	Cord Attached
ICB-Twin Tall	37600.0005	120/240	25	6000	6000	18.9 gal/hr	18.7 ft <sup>3</sup>	85.5 lbs	Yes

**Brewing Capacity:** Based upon incoming water temperature or 60°F/15.5°C (140°F/60°C) rise.

**Electrical:** Requires 3-wires plus ground service rated 120/240V, single phase 60Hz.

**Plumbing:** 20-90 psi (138-621 kPa). Supplied with 3/8" male flare fitting.



Bunn-O-Matic® Corporation - 1400 Stevenson Drive Springfield, Illinois 62703 • 800-637-8606 • 217-529-6601 • Fax 217-529-6644 • www.bunn.com

BUNN® practices continuous product research and improvement. We reserve the right to change specifications and product design without notice. Such revisions do not entitle the buyer to corresponding changes, improvements, additions or replacements for previously purchased equipment.

All dimensions shown in inches. Bunn-O-Matic Corporation owns all copyrights relating to materials in this publication. Please contact BUNN to request permission to reproduce any portion of this publication.