



1/2 – 1-1/4 H.P. DISPOSER MODELS

Heavy-duty disposer designed for continuous operation in restaurants, hotels, hospitals and cafeterias. Food waste including steak bones is quickly and efficiently removed with this labor-saving, self-cleaning, environmentally sound disposer.

SPECIFICATIONS

- **Grind Chamber:** Corrosion Resistant Stainless Steel
- **Mounting:** 3/4" (19.1 mm) rubber mounting above grinding chamber isolates sound and eliminates vibration. Mounting is enclosed in chrome plated covers for sanitation and appearance.
- **Motor:** 1/2 – 1-1/4 HP Induction Motor, 1725 RPM, totally enclosed to provide protection against outside moisture. Controlled power air flow cools motor for efficiency and longer life. Built-in thermal overload protection.
- **Cutting Elements:** Stationary and rotating shredding elements made from cast nickel chrome alloy for long life and corrosion resistance, designed for reverse action grinding.
- **Main Bearings:** Double-tapered Timken roller bearings provide a shock absorbing cushion.
- **Motor Seals:** Triple lip seal protects motor from water damage. Secondary spring-loaded oil seal provides double protection against water and loss of grease.
- **Finish:** All Stainless Steel and Chrome plated. Paint-free for lasting sanitation.
- **Warranty:** 1 year full warranty from date of installation.
- **A Disposer Package Includes:** 1 Mounting/Bowl Assembly, 1 Electrical Control, 1 Syphon Breaker, 1 Solenoid Valve, and 1 Flow Control Valve. The standard Flow Control Valve will be sent with the unit unless the optional valve is specified.



MODEL & HORSEPOWER/ELECTRICAL REQUIREMENTS

☐ SS-50 1/2 H.P.	☐ 115/208-230V, 60 Hz, 1 Ph, 8.4/4.0/4.2 amps, UL ☐ 208-230/460V, 60 Hz, 3 Ph, 2.0/2.2/1.1 amps, UL	☐ 115/208-230V, 60 Hz, 1 Ph, 8.4/4.0/4.2 amps, CSA ☐ 208-230/460V, 60 Hz, 3 Ph, 2.0/2.2/1.1 amps, CSA
☐ SS-75 3/4 H.P.	☐ 115/208-230V, 60 Hz, 1 Ph, 10.0/4.2/5.0 amps, UL ☐ 208-230/460V, 60 Hz, 3 Ph, 2.5/3.0/1.5 amps, UL ☐ 115/208-230V, 60 Hz, 1 Ph, 10.4/4.3/5.0 amps, CSA ☐ 208-230/460V, 60 Hz, 3 Ph, 2.5/3.0/1.5 amps, CSA	☐ 115/230V, 50 Hz, 3 Ph, 7.7/3.7 amps ☐ 230/460V, 50 Hz, 3 Ph, 2.7/1.4 amps ☐ 380V, 50 Hz, 3 Ph, 1.1 amps
☐ SS-100 1 H.P.	☐ 115/208-230V, 60 Hz, 1 Ph, 11.6/5.1/5.7 amps, UL ☐ 208-230/460V, 60 Hz, 3 Ph, 2.2/3.0/1.5 amps, UL ☐ 115/208-230V, 60 Hz, 1 Ph, 11.6/5.1/5.7 amps, CSA	☐ 208-230/460V, 60 Hz, 3 Ph, 2.2/3.0/1.5 amps, CSA ☐ 120/208-240V, 60 Hz, 1 Ph, 11.6/5.1/5.7 amps, NOM ☐ 100/200-230V, 50/60 Hz, 1 Ph, 10.4/5.2/5.4 amps
☐ SS-125 1-1/4 H.P.	☐ 115/208-230V, 60 Hz, 1 Ph, 12.8/5.9/6.6 amps, UL ☐ 208-230/460V, 60 Hz, 3 Ph, 2.6/3.3/1.9 amps, UL	☐ 115/208-230V, 60 Hz, 1 Ph, 12.8/5.9/6.6 amps, CSA ☐ 208-230/460V, 60 Hz, 3 Ph, 2.6/3.3/1.9 amps, CSA

NOTE: All amp ratings denote amp draw during a grind load.

ELECTRICAL CONTROLS



- ☐ AS-101 Control Center
"Aqua Saver"
(Auto-Reversing)



- ☐ CC-101 Control Center
(Auto-Reversing)



- ☐ CC-202 Control Center
(Auto-Reversing)



- ☐ Manual Reverse Switch
(Dual Direction)



- ☐ Manual Switch
(Single Direction)

Our products appear on **The KCL CADalog**
CD-ROM based CAD Foodservice Symbol
Library. More information is available from
Kochman Consultants, Ltd. at www.kclcad.com.



4700 21st STREET
RACINE, WI 53406
TEL: 800-845-8345
FAX: 262 554-3620

www.insinkerator.com



The Emerson logo is a
trademark and a service mark
of Emerson Electric Co.



Bowl Mounts