

7512

Value Series Slicer

Univex Corporation

WE RAISE THE BAR. WE SET THE STANDARD.

Project Item Number Quantity



7512 Value Slicer

Model:

> 7512: 1/2hp Manual Slicer





CERTIFIED BY NSF INTERNATIONAL TO MEET AND EXCEED THE NSF/ANSI 2012 STANDARDS

12" Precision slicing German hollow ground blade Unique smooth curve transitions to redirect

liquids away from controls and operator

Easily detachable carriage for easy cleaning

Features:

• Medium duty, moderate volume slicer

Maximum duty 4 hours a day

Capable of slicing moderate amounts of cheese

- Unique drip tray fence redirects liquids away from controls and operator towards distinctive concave base casting for easy cleaning
- Ergonomic comfort design operation
- Powerful 1/2 hp motor standard
- Adjustable slice thickness from 0 to 7/8"
- Easily removable sharpener for cleaning
- Quick and simple disassembly of carriage and feed grip for easy and thorough cleaning
- Sanitary polished and anodized aluminum construction
- Permanently mounted protective edge guard for operator safety
- Heavy duty 3-1/2 lb gravity fed grip

- Optional Accessories:

 Stainless steel blade
- Heavy duty clear plastic cover
- Stainless steel vegetable chute
- Sturdy stainless steel stand

Warranty:

• One year, on-site parts and labor



Univex Corporation www.Univexcorp.com


3 Old Rockingham Rd Salem, NH 03079 United States of America TEL: (800)258-6358 INTL TEL: (603)893-6191 FAX: (800)356-5614 INTL FAX: (603)893-1249


Printed in U.S.A. REV 1 01/2017 LH-575




Value Series Slicer

7512







Controls: Manual slice thickness knob, push button on/off,

attached blade sharpener

Drive Assembly: Belt driven

Blade diameter: 12" (30.4cm) razor sharp blade

Blade RPM: 345 RPM

Maximum slice thickness: .875" (2.2cm)

Maximum product size: Rectangular: 9.25" x 7.5" (24.5cm x 19cm)

Square: $7.5" \times 7.5"$ (19cm x 19cm)

Round: 8" (20.3cm)

Construction: Anodized, cast aluminum body for durability

and stunning looks

Nema #: 5-15-P

| Electrical Information (60Hz) | | | | | | |
|-------------------------------|---------|-------|------|------|-----------|--|
| | Voltage | Phase | Amps | RPM | hp(kW) | |
| Standard Voltage | 115 | 1 | 4.0 | 1680 | 1/2 (.37) | |
| Optional Voltage | 208-240 | 1 | 2.5 | 1680 | 1/2 (.37) | |

| Carriage Stroke | | | |
|-----------------|--|--|--|
| 11" (28cm) | | | |

| Shipping Information | | | | |
|----------------------|------------------|--|--|--|
| Net Weight | Shipping Weight | Overall Shipping Dimensions | | |
| 98.1lbs. (44.5Kg) | 106lbs. (48.1Kg) | 23" (55.9cm) H x 20" (50.8cm) W x 27" (66cm) D | | |



Univex Corporation www.Univexcorp.com

3 Old Rockingham Rd Salem, NH 03079 United States of America TEL: (800)258-6358 INTL TEL: (603)893-6191 FAX: (800)356-5614 INTL FAX: (603)893-1249