

4184 E. Conant St. Long Beach, CA 90808 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com

Project :	
Model #:	
Item #:	Qty:
Available W/H :	
Approval :	

Buffet Display Table

Food Prep Tables

J Series

Model: JBT-60



== FEATURES & BENEFITS ==_

■ Hot gas condensate system

Through Turbo Air's creative innovation, the condensate system surfaces have been specially treated to resist corrosion. This not only increases efficiency without the risk of refrigerant leakage from corrosion, but also prevents the overflow of condensate water.

■ Side mount compressor unit

By positioning the compressor on the side of the unit, refrigerators can now be serviced without being moved. Our innovative, front breathing feature also allows this model to provide high efficiency in narrow spaces.

Efficient refrigeration system

Turbo Air J series refrigerators are designed with oversized and balanced (CFC Free R-134A) refrigeration systems. These include efficient evaporators and condensers for faster cooling and greater efficiency.

■ Exterior & interior of the cabinet

The Turbo Air J series boasts a stainless steel exterior (galvanized steel back and bottom). Interior is stainless steel floor with AL sides, back and AL door liners. It guarantees the utmost in cleanliness and long product life. It can add a touch of style to the most refined setting.

■ High-density polyurethane insulation

The entire cabinet structure and solid doors are foamed-in-place using high density, CFC free polyurethane insulation.

Magnetic door gaskets

Magnetic door gaskets are of one piece construction, removable without tools for ease of cleaning and replacement.

Adjustable, heavy duty, PE(polyethylene) coated wire shelves

Ergonomically designed doors

Customers' fatigue fades away with easy grip handles and doors that open effortlessly. These features along with self-closing doors make this the ultimate choice in customer convenience.

Refrigerator holds 33°F ~ 39°F for the best in food preservation













-						intertest intertest			
	Model	Swing Door	CU./FT.	#of Shelves	#of Pans (1/3)	НР	AMPS	Crated Weight (lbs.)	L x D x H* (inches)
	JBT-60	2	15	2	12	1/3	8.9	235	59 x 271/2 x 283/4

(unit: inch)

Buffet Display Table

Model: JBT-60

ELECTRICAL DATA					
Voltage	115/60/1				
Plug Type					
Full Load Amperes	8.9				
Compressor HP	1/3				
Cord Length ft.	9.2				
Refrigerant	R-134A				
DIMENSIONAL DATA					
Ext. Length Overall in.	59 (1499mm)				
Ext. Depth Overall in.	27 _{1/2} (698mm)				
Ext. Height Overall in.*	283/4 (730mm)				
# of Doors	2				
# of Shelves	2				
# of Pans	12				
Net Capacity cu. ft.	15				
Net Weight lbs.	200				
Gross Weight lbs.	235				


Design and specifications subject to change without notice.

Actual shipping weight may differ due to extra packing materials for product protection.


■ WARRANTY: 2 Year Parts and Labor Warranty Additional 3 Year Warranty on Compressor

- Self-contained system
- Standard 4" swivel casters with locks on the front set
- 1/3 size condiment pan included
- 2.5" dia. casters available (optional) ½" diameter & 13 TPI
- Door locks available (optional)
- Legs available for all models (optional)
- Sneeze guard available (optional)
- Tray slide available (optional)
- Clear pan cover available (optional)

PLAN VIEW



PLAN VIEW



■ Tray Slide & Clear Pan Cover (Optional)



Clear Pan Covers

Size: 273/8 x 221/2

Material: Clear PC (Polycarbonate) Plastic

Qty: 2ea



Ver.201501




























^{*} Height does not include 5-7/8" for caster height.