

P250FW POCKETHERM WATERPROOF thermometer with fold out probe

CKETHER P250FW



Fast, accurate and waterproof thermometer with audible alarm plus flashing LEDs to indicate critical HACCP zones

GRD BEE

COLD HOLD

COMARK

COMARK

PIST form

P250FW Waterproof Pocketherm Folding Thermometer from Comark - it's fast, it folds, it bleeps, it's waterproof!

P250FW Pocketherm is fast and accurate - and accurate measurements can mean all the difference between safe and unsafe food, between freshness and spoilage of your products.

Designed for ease of use in the kitchen and other food production areas, the fold out thin tip steel probe (1.5mm) allows the user to select the best angle to take different temperatures.

Features

- Flashing LEDs plus buzzer for instant temperature indication
- Yellow for Hot Hold, Green for Cold Hold and Red for Ground Beef
- Probe can be angled for ergonomic use
- Range: -58°F to +482°F
- Resolution: 0.1°
- Accuracy: ±2°F
- Auto switch off to preserve battery life
- Battery life of more than 1000 hours
- Waterproof to IP65

Change your cooking experience with Pocketherm!

Comark Instruments 800-555-6658 sales@comarkUSA.com www.comarkUSA.com







Comark Instruments

P.O. Box 500 Beaverton, OR 97077, USA Tel: (503) 643 5204 Toll Free: (800) 555 6658 Fax: (503) 627 5311 Email: sales@comarkusa.com

Comark Instruments

52 Hurricane Way Norwich, Norfolk, NR6 6JB United Kingdom Tel: +44 (0) 207 942 0712 Fax: +44 (0) 207 942 0714 Email: sales@comarkinstruments.com



All rights reserved. Data subject to alteration without notice. All trademarks are the property of their respective owners. Modification of this document is not permitted without written permission from Comark Instruments.

P250FW POCKETHERM WATERPROOF thermometer with fold-out probe

Specifications P250FW

Sensors	Type T Thermocouple
Measurement range	-58°F to +482°F
Scales	°F
Displayed resolution	0.1°
System accuracy (+32°F to +104°F operating)	±2°F
Response time (T ⁹⁹)	5 seconds
Environment	
Operating temperature	-4°F to +122°F
Storage temperature	-22°F to +128°F
Humidity	10 to 90% non-condensing
HACCP Zones P250FW	
Cold Hold (Yellow)	Below +40° F
Hot Hold (Green)	+140°F to +165°F
Ground Beef (Red)	Above +165°F
Power	2 x alkaline AA cells (ANSI 15A IEC LR6)
Battery life	> 1000 hours
Enclosure rating	IP65
Auto switch-off	After 5 minutes

Warranty

All Comark instruments have a minimum one year warranty unless otherwise stated. The warranty for temperature probes is six months and all other probes are unwarranted because the conditions of use are beyond our control. The Comark Warranty covers manufacturing defects and component failure and applies worldwide. In line with our policy of continuous development, we reserve the right to alter any product specification without notice. Comark has an accredited UKAS (NIST equivalent) calibration laboratory for temperature and humidity measurement and offers full service and recalibration facilities.