

Project:	AIA#
Item:	
Location:	SIS#
Approved:	

P-SERIES TOP MOUNTED FREEZER

PF1-1AS Solid Door Roll-In Freezer

MODELS: PFI1-1AS



PFI1-1AS

OPTIONS & ACCESSORIES

- Stainless steel interior
- Remote option

3 Year Parts/Labor Warranty Additional 2 Year Compressor Warranty

CABINET CONSTRUCTION

- Stainless steel exterior
- Interior liner is made of corrosion resistant aluminum
- Full electronic control
- LED lighting standard
- Expansion Valve technology
- Self-closing door on cam-lift hinges, with 120° hold open feature
- One piece snap-in magnetic door gasket for positive seal
- Stainless steel breakers
- Reinforced stainless steel door ramps outside and cart guides inside
- Accepts carts up to 24 3/8" (W) x 26" (D) x 64 1/2" (H) (Cart not included)
- Wiper gasket at bottom of door seals door to ramp
- Door locks standard
- Anti-Microbial door handle
- Maintains product temperatures of 0° F and below

REFRIGERATIO N SYSTEM

- Refrigeration system uses R404A
- Automatic, electric defrost
- Epoxy coated evaporator coil

















MODEL	PFI1-1AS
EXTERNAL DIMENSIONAL DATA	
Width Overall	36 1/2"
Depth Overall with Handle	36 1/8"
Height Overall	84"
Number of Doors	1
Depth with Door Open 90°	65 3/4"
Door Opening (in)	27 3/4" x 65 1/4"
INTERNAL DIMENSIONAL DATA	
NET Capacity (cubic ft.)	35
Internal Width Overall (in)	31 1/4"
Internal Depth Overall (in)	26"
Internal Height Overall (in)	66 1/8"
ELECTRICAL DATA	
Full Load Amperes 115/208/60	8.8
REFRIGERATION DATA	
Horsepower	3/4
Capacity (BTU/Hr)*	2390
WEIGHT DATA	
Gross Weight (Crated lbs)	320 lbs
Height - Crated	88"
Width - Crated	45"
Depth - Crated	45"

Freezers powered by 115/208-230 volts are designed for field wiring (requires 3-wire electrical circuit, hard-wired).

P Series - Top Mount Roll-In Freezer

Models: PFI1-1AS



















