BLIXER[®]

robot @ coupe°

Blixer[®] 6

A

В



SALES FEATURES

Blixer 6 is designed to prepare texture-modified meals with either raw and cooked ingrediants in a minimum of time.

TECHNICAL FEATURES

Blixer 6. 3-phase. Power: 3 HP. Speeds: 1725 and 3450 rpm. 7 L stainless-steel bowl with handle, plus bowl-base, fine-serrated, twin-blade assembly. Totally leakproof lid with scraper arm. 3 - 23portions (7 oz).

Select your options at the back page, F part.

C TECHNICAL DATA	
Output power	3 HP
Electrical data	208-240V/60/3
Speeds	1725 and 3450 rpm
Dimensions (WxDxH)	11″ × 147/16″ × 20 13/16″ Cube: 3.68
Rate of recyclability	95%
Net weight	63 lbs
Nema #	L15-20P
Reference	BLIXER 6 - 208-240V/60/3

D

Number of 7 oz portions per service



Amount processed per operation

1 to 8 lbs

PRODUCT FEATURES / BENEFITS

MOTOR UNIT

E

- Industrial direct-drive (no belt) induction motor designed for intensive use
- Power 3 HP
- Stainless-steel motor shaft
- All-metal motor base
- Magnetic safety system, thermal failsafe
- Speeds 1725 and 3450 rpm

BLIXER® FUNCTION

- 7 L stainless-steel bowl with handle for better grip.
- Bowl-base blade assembly with two high-strength, stainlesssteel, fine-serrated blades for homogeneous processing - even for small amounts.
- Central lid opening for adding liquid or solid ingredients during processing.
- High heat and shock-resistant see-through lid to monitor processing from start to finish.
- · Leakproof lid and bowl unit with bowl scraper arm and lid wiper.
- All parts are dishwasher-safe and can easily be removed for cleaning.

STANDARD ATTACHMENTS

- 7 L bowl with lid.
- Bowl scraper arm and lid wiper.
- Blade assembly with two fine-serrated, stainless-steel blades and a detachable cap.

STANDARDS ETL electrical and sanitation Listed/ cETL (Canada)



Specification sheet

www.robotcoupeusa.com

Update : October 2017

Robot Coupe USA, Inc. 264 South Perkins - Ridgeland, MS 39157 PH: 601-898-8411 - Toll free: 800-824-1646 - Fax: 601-898-9134 info@robotcoupeusa.com



BLIXER[®]



Blixer[®] 6


F


OPTIONAL ATTACHMENTS


- Fine serrated edge stainless steel "S" blade assembly Ref. 27169
- 7 L Stainless steel bowl assembly Ref. 27166

ELECTRICAL DATA

208-240V/60/3 – delivered with cord and plug.







Blixer[®] 6

G