"CL" Series Automatic Coffee Urns

- ✓ Automatic Refill Automatically replenishes the Urn jacket with fresh water as soon as it starts running low giving you piping hot water on demand
- ✓ Automatic Agitation With the "CL" Series, simply "Push and Hold" button for any specified period of time to agitate the coffee.
- ✓ Electro Mechanical Selector Timer -
- ✓ Accurate Temperature Control Keeps coffee hot all the time.
- ✓ Tomlinsons "No Drip" Faucet



		Cups / Hr.		Dimensions			Ship
Model #	Description	Gal / Hr.	Electric	Depth	Width	Height	Weight
CL75	3 gal. Single	432 18	7KW at 120/240-29 Amps 5.3 KW at 120/208-25 Amps AC 50/60HZ single Phase - 3 wire		21 1/2"	28 1/2"	70 lbs.
CL100	3 gal. Twin	600 25	7 KW at 120/240-29 amps 5.3 KW at 120/208-25 amps AC 60HZ single phase - 3 wire	17 1/2"	33 1/2"	28 1/2"	90 lbs.
CL200	6 gal. Twin	720 60	10 KW at 120/240-42 amps 7.5 KW at 120/208-36 amps AC 60 HZ single phase - 3 wire	19 1/2"	37 1/2"	33"	130 lbs.

Plumbing: .1/4"" water line required Special Voltage: 220V, 380V, 440V - consult factory for details **Options:** 3 phase - 4 wire; Double service with gauge glass

Manual Pour Over Coffee Urns

Manual Refill Water Valve
If a water outlet is available, this feature gives
you the option to plumb water directly into the
um jacket.

In a class by itself, the MPO coffee urns are unique in their ability to brew coffee where water lines are not available.

Constructed of high quality stainless steel, enjoy years of brewing endless gallons of coffee with this urn.

Optional: Truck Board



Marial #	Coffee	Water	Natural Gas	Propane Gas	Elec	Ship	
Model #	Capacity	Capacity	BTU / hr. @7" W.C.	BTU/hr. @11" W.C.	1 Phase	3 Phase	Weight
MPO 3	3 gal. Single	8 gal.	13,000	13,000	3 KW, 12.5 Amps	4 KW, 9.6 Amps	50 lbs.
MPO 6	6 gal. Single	10 gal.	13,000	13,000	5 KW, 20.8 Amps	5 KW, 12.0 Amps	60 lbs.
MPO 303	3 gal. Twin	13 gal.	29,000	24,500	5 KW, 20.8 Amps	5 KW, 12.0 Amps	80 lbs.
MPO 606	6 gal. Twin	18 gal.	29,000	24,500	7 KW, 29.2 Amps	8 KW, 19.3 Amps	92 lbs.

Depth: 17 ¹/₂"

Width: MPO 3 and MPO 6 - 16" MPO 303 and MPO 606 - 28"

Plumbing: 1/2" water line required

For Gas: Specify Natural or L.P.

Height: MPO 3 and MPO 303 - 27 ¹/₂"

MPO 6 and MPO 606 - 32 1/2" **Electrical:** 208/240V; Specify 1 phase or 3 phase