



Compact, Gravity Feed, Manual Slicers

- ✓ Poly V Belt Driven System
- ✓ Constructed of Heavy Duty Anodized Aluminum
- ✓ Cutting Blade - Special chromium-plated steel blade, ground and hardened for long service life.
- ✓ Sharpener - Built-in sharpening device with adjustable emery grindstones.
- ✓ Cam Control Knob - Adjusts the cut thickness of the product up to $\frac{9}{16}$ " ; allows for decimal adjustments as well.
- ✓ Carriage - runs on a series of self lubricated ball bearings giving you a smooth glide as you cut.
- ✓ Easy To Clean

Model #	Blade Size	Cut Thickness Adjustable up to:	H.P.	Max. Width / Stroke	Max. Length / Stroke	Depth	Width	Height	Ship Weight
Economy Models									
EPS-9	9"	$\frac{7}{16}$ "	$\frac{1}{4}$	6 $\frac{1}{8}$ "	7 $\frac{1}{2}$ "	18 $\frac{1}{2}$ "	15 $\frac{3}{8}$ "	15 $\frac{3}{4}$ "	33 lbs.
EPS-10	10"	$\frac{1}{2}$ "	$\frac{1}{4}$	6 $\frac{1}{4}$ "	8 $\frac{1}{8}$ "	21 $\frac{1}{2}$ "	20 $\frac{7}{8}$ "	18 $\frac{3}{8}$ "	50 lbs.
EPS-12	12"	$\frac{1}{2}$ "	$\frac{1}{3}$	8 $\frac{1}{2}$ "	9 $\frac{7}{8}$ "	25 $\frac{1}{4}$ "	24"	20"	57 lbs.
Heavy Duty Models									
HDPS-12	12"	$\frac{9}{16}$ "	$\frac{1}{3}$	8 $\frac{1}{2}$ "	9 $\frac{7}{8}$ "	25 $\frac{3}{8}$ "	25 $\frac{1}{4}$ "	23 $\frac{1}{4}$ "	84 lbs.
HDPS-14	14"	$\frac{9}{16}$ "	$\frac{1}{2}$	9 $\frac{7}{8}$ "	11"	29 $\frac{3}{4}$ "	26"	27 $\frac{1}{4}$ "	110 lbs.

Electrical: 120V, 60 HZ, Single phase