



STAINLESS STEEL EVERYDAY BUFFET ICE-COOLED TABLES WITH ENCLOSED BASE



| | |
|------------------|--------------|
| Item #: _____ | Qty #: _____ |
| Model #: _____ | |
| Project #: _____ | |

FEATURES:

- 4" Swivel Casters, with two brakes
- Double sided sneeze guard & side panels
- Fiberglass insulation
- Removable access panel
- Adapter bars for 12" x 20" food pans included

MATERIAL:

- TOP:** 18 gauge #304 stainless steel welded frame
- BODY:** 20 gauge steel available in matte black vinyl clad
- SNEEZE GUARD:** 1/4" Thermoplastic Polymer
- INSULATION:** Fiberglass insulation
- LINERS:** 8" deep, 18 Gauge stainless steel

PLUMBING:

- 1" I.P.S. drain



B4-CPU-SB Shown

| Model | Length (L) | Inside Well (A) | Weight (lbs.) | Cubic Feet |
|-------------|------------|-----------------|---------------|------------|
| B2-CPU-B-SB | 31-13/16" | 27-5/16" | 235 | 53 |
| B3-CPU-B-SB | 47-1/8" | 42-5/8" | 260 | 76 |
| B4-CPU-B-SB | 62-7/16" | 58" | 320 | 97 |
| B5-CPU-B-SB | 77-3/4" | 73-1/4" | 360 | 119 |

Optional Accessories



10" Wide Stainless Steel Tray Shelves

STATIONARY DROP-DOWN

| Model | Model | Length | Approx Wt. | Cu. ft. |
|-------|--------|----------|------------|---------|
| TTS-2 | TTS-2D | 31.8125" | 14 lbs. | 3 |
| TTS-3 | TTS-3D | 47.125" | 16 lbs. | 4 |
| TTS-4 | TTS-4D | 62.4375" | 18lbs. | 5 |
| TTS-5 | TTS-5D | 77.75" | 21 lbs. | 6 |

**Visit our website
for more
Everyday Buffet
Accessories!**

10" Wide Stainless Steel Tray Rails

STATIONARY DROP-DOWN

| Model | Model | Length | Approx Wt. | Cu. ft. |
|-------|--------|----------|------------|---------|
| TTR-2 | TTR-2D | 31.8125" | 14 lbs. | 3 |
| TTR-3 | TTR-3D | 47.125" | 16 lbs. | 4 |
| TTR-4 | TTR-4D | 62.4375" | 18lbs. | 5 |
| TTR-5 | TTR-5D | 77.75" | 21 lbs. | 6 |



Customer Service Available To Assist You 1-800-645-3166 8:30 am - 8:00 pm E.S.T.

For Orders & Customer Service:
Email: customer@advancetabco.com or Fax: 631-242-6900

For Smart Fabrication™ Quotes:
Email: smartfab@advancetabco.com or Fax: 631-586-2933

DIMENSIONS and SPECIFICATIONS

TOL $\pm .125"$

ALL DIMENSIONS ARE TYPICAL

