

DRYING RACKS



Item Number: DXIRDSIF

Item Numbers

Insulated Tray Systems

- DXIRDSIF Full size 72"
- DXIRDSIH Half size 36"

Application

The open wire shelving allows ample ventilation for drying of many different sizes of trays.

Structural Design

Dinex[®] Drying Racks are a combination of four heavy-duty chromed wire shelving, posts and three-sided enclosure panels. The open wire shelving allows ample ventilation for drying of trays. Units are fully assembled and ready for operation. Height of both drying racks is 68" (173cm).

Have four 5" stem swivel casters which are non-marking polyurethane and come with 3" donut bumpers to provide the right combination of roll-ability and maneuverability to suit your requirements.

IRDSI Capacities

	Full	Half
Solar Covers	68	34
Solar Servers	156	78
Ultima Covers	96	48
Ultima Servers	156	78
Gemini Covers (Full)	96	48
Gemini Covers (Partial)	192	96
Gemini Servers	112	56
Omni Covers	192	96
Omni Servers	192	96
DX1089RS03	69	33

Note: Gemini and Omni Covers are stored 2 per shelf.

Warranty

One year parts and labor.

DRYING RACKS

Items and Dimensions

ITEM NUMBER	MODEL NUMBER	LENGTH	DEPTH	HEIGHT	SHIP WEIGHT	SHIP CUBE
DXIRDSIF	IRDSI/F	72" (182.7cm)	24" (60.9cm)	68" (172.6cm)	195 lb. (88kg)	77.6
DXIRDSIH	IRDSI/H	36" (91.4cm)	24" (60.9cm)	68" (172.6cm)	124 lb. (56kg)	36.4



Please confirm that you have the most current specification sheet by visiting www.dinex.com.
Dinex® reserves the right to change specifications and product design without notice.
Such revisions do not entitle the buyer to corresponding changes, improvements, additions or replacements for previously purchased equipment.

DINEX®

Building 2, Suite 106
628 Hebron Avenue
Glastonbury, CT 06033
800.523.9752 Fax: 860.652.3135
www.dinex.com