Project:

Item Number:

Quantity:

SIGNATURE SERVER® CLASSIC COLD FOOD STATIONS

Signature Server® Classic Cold Food Stations

DESCRIPTION

Signature Server® Classic is the choice when functionality and modular ease of use are your top priorities. Signature Server® Serving Equipment is an industry standard, with updated features to better serve the operator.

FEATURES

- ❑ Vollrath's Signature Server® Classic Cold Food Stations are available in non-refrigerated and refrigerated models
- ❑ Reinforced stainless steel unibody construction provides extra durability in a lightweight, mobile base
- ❑ Base is 18-gauge 300 Series stainless steel clad with black laminate. Optional colors and finishes are also available.
- ❑ Top is one-piece 18-gauge 300 Series stainless steel
- ❑ Optional 14 gauge work surface available
- ❑ Well constructed of 18-gauge 300 Series stainless steel
- ❑ Foamed-in-place polyurethane insulation
- ❑ R134A refrigerant
- ❑ Drain hose on operator side of base
- ❑ Heavy-duty 4" (10 cm) swivel casters with brakes
- ❑ 8 ft. (2.4 m) cord
- ❑ Non-refrigerated models are NSF2
- ❑ Refrigerated models are not NSF
- ❑ Storage not available on 46" models

Note: Signature Server® equipment orders cannot be cancelled or returned.

WARRANTY: All models shown come with Vollrath's standard warranty against defects in materials and workmanship. For full warranty details, please refer to the Vollrath Equipment and Smallwares Catalog.

MODELS AND OPTIONS

Base

Width	Style	Height / Item No 27 (69)	30 (76)	34 (86)
46" (117)	Non-Refrig	36243	36143	37043
	Refrig	36245	36145	37045
60" (152)	Non-Refrig	36260	36160	37060
	Refrig	36265	36165	37065
74" (188)	Non-Refrig	36270	36170	37070
	Refrig	36275	36175	37075
88" (224)	Non-Refrig	–	–	98707
	Refrig	–	–	98708

Options

Color (Black is standard) Matte Laminate	Wood Grain	Stainless Steel
36680	36687	36693
36681	36688	36694
36682	36689	36695
98835	98835	93836

Breath Guards	Lighting	Accessories
Choose from: Progressive, Contemporary, Traditional, Classic Cafeteria, Classic Economy Buffet, Access® and Classic Speed Serve. See Breath Guard spec sheets for selection information.	**Choose from:** Incandescent, or fluorescent lights. See Breath Guard spec sheets for selection information.	**Choose from:** plate rests, cutting boards, end shelf, tray slides, storage modules, false bottoms, bag in box, stationary legs. See Accessories spec sheet for selection information.

Use only Vollrath accessories, including breath guards. Vollrath is not responsible for the fit or installation of custom made accessories and components. Custom accessories and components may void agency listings.

Agency Listings

c UL us LISTED NSF

Refrigerated models are not NSF

Due to continued product improvement, please consult www.vollrathco.com for current product specifications.

Approvals	Date

Setting the Standard™

www.vollrathco.com

The Vollrath Company, L.L.C.
1236 North 18th Street
Sheboygan, WI 53081-3201 U.S.A.
Customer Service: 800.628.0830
Canada Customer Service: 800.695.8560
Main Fax: 800.752.5620 or 920.459.6573

Technical Services: 800.628.0832
Technical Services Fax: 920.459.5462

SIGNATURE SERVER® CLASSIC COLD FOOD STATIONS

DIMENSIONS Dimensions shown in inches (cm).



Top View



Operator Side View



End View

Model		(A) Pan Width	(B) Overall Width	(B) Height
Non-Refrig	Refrig			
36243	36245	37¾ (95.9)	46 (117)	27 (69)
36143	36145			30 (76)
37043	37045			34 (86)
36260	36265	50¼ (127.6)	60 (152)	27 (69)
36160	36165			30 (76)
37060	37065			34 (86)
36270	36275	63 (160)	74 (188)	27 (69)
36170	36175			30 (76)
37070	37075			34 (86)
–	–	75¾ (192.4)	88 (224)	27 (69)
–	–			30 (76)
98707	98708			34 (86)

NON-REFRIGERATED ELECTRICAL SPECIFICATIONS

Base Unit Voltage	Lighting Choice	Width / Total Amps				Plug
		46 (117)	60 (152)	74 (188)	88 (224)	
120	Fluorescent	0.6	0.5	0.5	0.3	5-15P
	Incandescent	0.6	0.8	1	1.3	5-15P
	None	–	–	–	–	–

Receptacle

120V

5-15R

REFRIGERATED ELECTRICAL SPECIFICATIONS

Base Unit Voltage	Lighting Choice	Width / Total Amps				Compressor (HP)	Plug
		46 (117)	60 (152)	74 (188)	88 (224)		
120	Fluorescent	4.1	5.5	5.5	7.8	¼	5-15P
	Incandescent	4.2	6	6.2	8.4	¼	5-15P
	None	3.8	5.2	5.2	7.2	¼	5-15P

Receptacle

120V

5-15R

The Vollrath Company, L.L.C.

VOLLRATH® Setting the Standard™

www.vollrathco.com

The Vollrath Company, L.L.C.
1236 North 18th Street
Sheboygan, WI 53081-3201 U.S.A.
Customer Service: 800.628.0830
Canada Customer Service: 800.695.8560
Main Fax: 800.752.5620 or 920.459.6573

Technical Services: 800.628.0832
Technical Services Fax: 920.459.5462

©2012 The Vollrath Company L.L.C.

Form Number L35359 5/12
Printed in USA