







KIT SOLUTIONS	50 = 1/2" ID 75 = 3/4" ID 100 = 1" ID 125 = 1-1/4" ID	BTU/hr Minimum Flow Capacity*						
	PART NUMBER		THE BLUE HOSE™	SnapFast® QUICK-DISCONNECT	Swivel MAX® 1st SWIVEL	Swivel MAX® 2nd SWIVEL	Safety Quik® VALVE	RESTRAINING CABLE
Standard Kit (KIT)¹ The Dormont Blue Hose™ SnapFast Quick-Disconnect Restraining Cable	1650KIT36	77K	✓	✓				✓
	1650KIT48	68K	✓	✓				✓
	1650KIT60	60K	✓	✓				✓
	1675KIT36	218K	✓	✓				✓
	1675KIT48	180K	✓	✓				✓
	1675KIT60	158K	✓	✓				✓
	16100KIT36	379K	✓	✓				✓
	16100KIT48	334K	✓	✓				✓
16100KIT60	294K	✓	✓				✓	
Single Swivel MAX Kit (KITS)² The Dormont Blue Hose™ SnapFast Quick-Disconnect One Swivel MAX Swivel Restraining Cable	1650KITS36	72K	✓	✓	✓			✓
	1650KITS48	63K	✓	✓	✓			✓
	1650KITS60	56K	✓	✓	✓			✓
	1675KITS36	203K	✓	✓	✓			✓
	1675KITS48	167K	✓	✓	✓			✓
	1675KITS60	147K	✓	✓	✓			✓
	16100KITS36	353K	✓	✓	✓			✓
	16100KITS48	310K	✓	✓	✓			✓
16100KITS60	274K	✓	✓	✓			✓	
Double Swivel MAX Kit (KIT2S)³ The Dormont Blue Hose™ SnapFast Quick-Disconnect Two Swivel MAX Swivels Restraining Cable	1650KIT2S36	69K	✓	✓	✓	✓		✓
	1650KIT2S48	60K	✓	✓	✓	✓		✓
	1650KIT2S60	54K	✓	✓	✓	✓		✓
	1675KIT2S36	193K	✓	✓	✓	✓		✓
	1675KIT2S48	160K	✓	✓	✓	✓		✓
	1675KIT2S60	140K	✓	✓	✓	✓		✓
	16100KIT2S36	336K	✓	✓	✓	✓		✓
	16100KIT2S48	295K	✓	✓	✓	✓		✓
16100KIT2S60	261K	✓	✓	✓	✓		✓	
Safety Quik Kit (KITCF)⁴ The Dormont Blue Hose™ Safety Quik Quick-Disconnect Restraining Cable	1650KITCF36	77K	✓				✓	✓
	1650KITCF48	68K	✓				✓	✓
	1650KITCF60	60K	✓				✓	✓
	1675KITCF36	218K	✓				✓	✓
	1675KITCF48	180K	✓				✓	✓
	1675KITCF60	158K	✓				✓	✓
	16100KITCF36	379K	✓				✓	✓
	16100KITCF48	334K	✓				✓	✓
16100KITCF60	294K	✓				✓	✓	
Safety Quik Single Swivel MAX Kit (KITCFS)⁵	1650KITCFS36	72K	✓		✓		✓	✓
	1650KITCFS48	63K	✓		✓		✓	✓
	1650KITCFS60	56K	✓		✓		✓	✓
	1675KITCFS36	203K	✓		✓		✓	✓
	1675KITCFS48	161K	✓		✓		✓	✓
	1675KITCFS60	147K	✓		✓		✓	✓
	16100KITCFS36	353K	✓		✓		✓	✓
	16100KITCFS48	310K	✓		✓		✓	✓
16100KITCFS60	274K	✓		✓		✓	✓	

¹ Includes Full Port Gas Valve and (2) 90° Street Elbows

² Includes Full Port Gas Valve and (1) 90° Street Elbow

³ Includes Full Port Gas Valve

⁴ Includes (2) 90° Street Elbows

⁵ Includes (1) 90° Street Elbow

Indicates most commonly stocked item

*BTU/hr Minimum Flow Capacity (0.64 Sp.Gr., 1000 BTU/ft³ Natural Gas at 0.5" wc pressure drop)

ADDITIONAL CONFIGURATIONS ARE AVAILABLE IN OUR CATALOG.



Add PS to the end of any part number to include the Safety-Set® wheel placement system



We guarantee our commercial gas connectors for the life of the original appliance to which it is connected.