



Performance Features:

Low Temperature Cook and Hold Oven With Smoker Feature

- ◇ Use settings or use manually
- ◇ Variable smoke time
- ◇ Switches automatically from Smoke to Cook to Hold mode
- ◇ Separate temperature displays for Cook and Hold modes
- ◇ Preset 12 menu selections
- ◇ Cook by internal probe (included)
- ◇ Cam door latch provides positive close and tight seal
- ◇ Smoker tray with extended handle allows for easy access for loading wood chips and cleaning



Exclusive
2-compartment
smoke box provides
longest burn time
in the industry without
wood chip refill.



Capacity:
Spacings @ 3"
4 18" x 26" Trays
8 12" x 20" Pans
4 GN 2/1-65mm
8 GN 1/1-65mm



CH-4-SK



Low Temperature Cook and Hold Oven With Smoker Feature

- ◇ All stainless steel
- ◇ All welded construction - no rivets
- ◇ Welded base frame
- ◇ Polyurethane casters
- ◇ Silicon Gasket - High heat durable, long lasting and easy-to-clean
- ◇ Cord pocket - allows for multi-directional use
- ◇ Venting with door baffles
- ◇ Drip tray
- ◇ Fully insulated throughout
- ◇ Universal tray slides
- ◇ Two year limited warranty

Specifications:

Electrical Data:


CH-4-SK, CH-4-SK-S		
VOLTS	120	208
WATTS	2450	2450
AMPS	20.4	11.8
HERTZ	50/60	50/60
PHASE	Single	Single
PLUG: USA	5-30P	6-15P
PLUG: CANADA	5-30P	OR 6-20P

CH-6-SK, CH-6-SK-S		
VOLTS	208	220-240
WATTS	2450	2450
AMPS	11.8	10.2
HERTZ	50/60	50/60
PHASE	Single	Single
PLUG: USA	6-15P	6-15P
PLUG: CANADA	OR 6-20P	OR 6-20P

CH-9-SK, CH-9-SK-S		
VOLTS	208	220-240
WATTS	3450	3450
AMPS	16.6	14.4
HERTZ	50/60	50/60
PHASE	Single	Single
PLUG: USA	6-20P	6-20P
PLUG: CANADA	6-30P	6-20P

Optional Accessories:

- All swivel or larger casters
- Push - pull bar handles
- Security panel for controls
- Extra tray slides
- Floorlock (requires 6" casters)
- Menu card holder
- Shelves



Smoker Oven MODEL NUMBER	TRAY/PAN SLIDES PROVIDED	CAPACITIES @ 3" Spacings (76mm)								OVERALL EXTERIOR DIMENSIONS IN. (mm)			CLASS 100		
		18 x 26	12 x 20	14 x 18	12 x 18	20 x 22	10 x 20	GN 2/1	GN 1/1	HIGH "H"	DEEP "D"	WIDE "W"	NO. OF DOORS	CASTER SIZE	SHIP WT. LBS. (KG)
CH-4-SK	4	4	8	8	8	4	8	4	8	30" (762)	39.25" (997)	27" (686)	1	5"	225 (101)
CH-4-SK-S NO CASTER MODEL	4	4	8	8	8	4	8	4	8	25" (635)	39.25" (997)	27" (686)	1	NO CASTERS	215 (97)
CH-6-SK	6	6	12	12	12	6	12	6	12	36" (914)	39.25" (997)	27" (686)	1	5"	370 (167)
CH-6-SK-S NO CASTER MODEL	6	6	12	12	12	6	12	6	12	31" (787)	39.25" (997)	27" (686)	1	NO CASTERS	360 (162)
CH-9-SK	9	9	18	18	18	9	18	9	18	45" (1143)	39.25" (997)	27" (686)	1	5"	380 (171)
CH-9-SK-S NO CASTER MODEL	9	9	18	18	18	9	18	9	18	40" (1016)	39.25" (997)	27" (686)	1	NO CASTERS	370 (167)

All rights reserved. All specifications subject to change without notice. Errors subject to correction. © 13 Food Warming Equipment Company, Inc.

FOOD WARMING EQUIPMENT COMPANY, INC
5599 Highway 31 West • Portland, TN 37148 | 800 222 4393 | 815 459 7500 | Fax: 815 459 7989 | www.FWE.com

KaTom Restaurant Supply, Inc.