



PROJECT:	MODEL:	QUANTITY:	ITEM NO:

# HEATED HOLDING & HUMIDIFIED CABINETS

## For 12" x 20" Pans, 18" x 13" Trays and GN 1/1 Containers

### HUMIDIFIED "MT-1220" SERIES

### Hold hot food fresh and ready to serve, longer than ever before!

- 1** Easy to use - upfront and recessed electronic control panel has separate, easy to read and set, air moisture and air temperature controls
- 2** Built-in humidity system balances moisture and air with controlled heat and humidity capabilities - allows for greater control of holding food environment for longer holding periods
- 3** Removable humidity pan: 12" x 20" pan provides large water reservoir - removable, easy to clean and replaceable
- 4** MT-1220 series accommodates shallow and deep 12" x 20" pans, 18" x 13" trays and GN1/1 containers. Unique pan slide racks' front edges are relieved for easy loading, one piece die stamped stainless steel for extra strength, and removable for easy cleaning
- 5** Constructed of stainless steel, with welded base frame for added strength and durability - fully insulated cabinet and door provide energy efficient heating and longer holding times
- 6** Field reversible door - flexible installation options for kitchen layout
- 7** Magnetic work flow door handle - ergonomically accomodates kitchen staff and servers at varying heights

**\*Two year limited warranty**



**MT-1220-15**



**MT-1220-10**

(Shown with Left Hand Door Hinging Optional Accessory)



Control Panel



Humidity Pan



Convenient Fixed Rack Assembly



Work Flow Door Handle





CE IP X4



PROJECT:	MODEL:	QUANTITY:	ITEM NO:
----------	--------	-----------	----------

# SPECIFICATIONS: HEATED HOLDING & HUMIDIFIED CABINETS



MODEL NUMBER	CAPACITIES OF 12" x 20" or GN 1/1 PANS [A]						OVERALL EXTERIOR DIMENSIONS IN. (mm) (Height Includes Casters)			CLASS 100		SHIP WT. LBS. (KG)
	2.625" FIXED SPACINGS			66.7mm FIXED SPACINGS			HIGH "H"	DEEP "D"	WIDE "W"	NO. OF DOORS	CASTER SIZE	
	DEPTH 12"x20" PANS			DEPTH GN 1/1 PANS								
MT-1220-8	8	4	2	8	4	2	39.5" (1003)	26.5" (673)	21.5" (546)	1	5"	170 (77)
MT-1220-10	10	5	3	10	5	3	45.5" (1080)	26.5" (673)	21.5" (546)	1	5"	190 (86)
MT-1220-6-6 Split Cavity	12 6 ea	6 3 ea	4 2 ea	12 6 ea	6 3 ea	4 2 ea	63.5" (1613)	26.5" (673)	21.5" (546)	2	5"	265 (116)
MT-1220-15	15	7	5	15	7	5	57.5" (1461)	26.5" (673)	21.5" (546)	1	5"	245 (111)
MT-1220-20	20	10	6	20	10	6	43" (1092)	26.5" (673)	38.5" (978)	2	5**	320 (145)
MT-1220-30	30	14	10	30	14	10	57.5" (1461)	26.5" (673)	38.5" (978)	2	5**	350 (159)
MT-1220-45	45	21	15	45	21	15	57.5" (1461)	26.5" (673)	55.5" (1410)	3	5**	450 (204)

[A] Combinations of deep and shallow pans may be used with varying capacities. Many half-size pans may also be used. For one-third size pans, consult factory. Also accommodates one (1) 18" x 13" x 1.5" tray per set of slides.  
 All MT-1220 models are available with the **Pass-thru Door** [add "P"], **See-thru Lexan Door** [add "L"] and **Dutch Doors** [add "D"] optional accessories. **Note:** Dutch Doors are 2 half size doors on full-size models.  
**MT-1220-6-6 Split Cavity Capacity:** provides 2 compartments; each with separate controls; 5 pair of tray slides are provided in each compartment.  
 \*MT-1220-20, MT-1220-30 and MT-1220-45 are standard with all swivel casters.

ELECTRICAL DATA						
	MT-1220-8 MT-1220-10 MT-1220-15		MT-1220-20 MT-1220-30 MT-1220-45		MT-1220-6-6 Split Cavity	
VOLTS	120	220-240	120	220-240	120	220-240
WATTS	1650	2133	1900	2252	2300	3075
AMPS	13.8	8.9	15.8	9.4	19.2	12.8
HERTZ	50/60	50/60	50/60	50/60	50/60	50/60
PHASE	Single	Single	Single	Single	Single	Single
PLUG USA	5-15P	6-15P	5-20P	6-15P	5-20P	6-15P
PLUG CANADA	5-20P	6-15P	5-20P	6-15P	5-30P	6-20P

Dedicated circuit.

**CONSTRUCTION.** Helicarc welded, single unit construction of stainless steel; 20-gauge polished exterior, 22-gauge stainless steel interior with easy-to-clean covered corners. Welded tubular base frame shall be 1" square, heavy gauge stainless steel tubing, with 10-gauge stainless steel reinforcing stress plates at corners.  
**INSULATION.** "Ultra-Guard" UG-26 high density fiberglass insulation throughout; top, back, bottom, sides and door(s).  
**HANDLES.** Form grip flush-in-wall hand grips recessed mounted on each side of unit.  
**DOORS AND LATCHES.** Flush mounted, field reversible, stainless steel insulated doors. High temperature gasket sealed; gasket shall be cabinet mounted. Each door shall have two (2) heavy-duty edgemarked die cast hinges and a magnetic work flow door handle. The hinge and latch mountings are reinforced with stainless steel backing plates. Models MT-1220-20, MT-1220-30, and MT-1220-45 are not field reversible.

**CASTERS.** Maintenance free polyurethane tire casters in a configuration of two (2) rigid and two (2) swivel with brake. MT-1220-20, MT-1220-30 and MT-1220-45 shall have a caster configuration of four (4) swivel with brake. Casters shall have a reinforced yoke mounted to 10-gauge caster plate. The caster mounting plate shall be secured to a 10-gauge stainless steel reinforcing stress plate via welded in place stainless steel studs. The reinforcing stress plates shall be welded to the heavy gauge tubular frame of the unit.  
**TRAY SLIDES.** Stainless steel racks shall be one piece die stamped channel-type pan slides at 2.625" (66.7 mm) spacings to accommodate either deep or shallow 12" x 20" or GN 1/1 pans (at varying capacities - see chart). Racks are removable without tools for cleaning. Racks shall lift off heavy-duty stainless steel supports.

**MOISTURE-TEMP SYSTEM/CONTROLS.** Built in humidified holding system shall include two (2) separate long life Incoloy nickel-chromium alloy heating elements per cavity; separate, adjustable controls shall be provided for each function. One to control the interior air temperature, and one to control the interior air moisture. 12" x 20" stainless steel water reservoir shall be removable for ease of cleaning/sanitation. Built-in drip trough has removable drain plug. System shall have a Hi-Temp, self-lubricated, impedance protected fan-cooled blower motor for moist air distribution. Controls shall be electronic, up-front, recessed and eye-level for convenience and safety and shall include a full range thermostat adjustable to actual temperature. Thermostat shall include temperature scale marked in ten degree increments (F/C) from 90° to 190°F (32° to 88°C). An operational range thermometer, adjustable moisture control (moist to crisp), 20 amp ON/OFF power switch, humidity cycle light, and thermostat cycling light shall also be included.

**ELECTRICAL CHARACTERISTICS.** 3 wire grounded tri-directional power cord and plug, rear mounted for safety. See electrical data chart above for amperage and receptacle configuration. Dedicated circuit.  
**INSTALLATION.** Unit should not be installed in an area where adverse environmental conditions are present.

- Optional Accessories**
- ELECTRICAL**
    - 220 volt, 50/60 Hz single phase
    - Timer
    - Element upgrade
  - DOORS**
    - Dutch doors
    - See-thru Lexan door
    - Key locking door latch
    - Paddle latch
    - Left hand door hinging
    - Glass doors
  - SPACINGS**
    - Custom pan slide spacings
    - Shelves
  - CASTERS**
    - All swivel or larger casters
  - EXTRAS**
    - Full extension bumper
    - Heavy-duty push/pull handles
    - Top corner bumpers (set of 4)
    - Security packages
    - Cord winder bracket

FWE products may be covered under one or more of the following U.S. patents: 288,299; 238,300; 3,952,609; 4,192,991. All rights reserved. All specifications subject to change without notice. Errors subject to correction.  
 © 16 Food Warming Equipment Company, Inc. R.16.02



**FOOD WARMING EQUIPMENT COMPANY, INC.**  
 5599 HWY. 31 W. Portland, TN 37148  
 800.222.4393 | 815.459.7500 | Fax: 815.459.7989  
 www.FWE.com | sales@fwe.com

