EAGLE GROUP®
Profit from the Eagle Advantage®

Specification Sheet

Item No.: _____
Project No.: _____
S.I.S. No.: _____

Wire Shelving Starter Units and Add-On Units

Short Form Specifications

Eagle Wire Shelving (EAGLEBrite® Zinc, Chrome, Valu-Master® Gray Epoxy, Valu-Gard® Green Epoxy, EAGLEgard® Green Epoxy, Stainless Steel), (Starter/Add-On) Unit, model _____. Patented QuadTruss® design wire shelves, with numerically calibrated grooved posts in 1″ increments, leveling feet, and tapered split sleeves.

MODELS:

❑ ***S4-63-**** ❑ ***S5-74-**** ❑ ***A4-63-**** ❑ ***A5-74-****
❑ ***S4-74-**** ❑ ***S5-86-**** ❑ ***A4-74-**** ❑ ***A5-86-****

** See charts on back for complete model numbers.*

four-shelf starter unit

five-shelf add-on unit

Design and Construction Features

- Patented QuadTruss® design (patent #5,390,803) makes Eagle shelves up to 25% stronger and provides a retaining ledge for increased storage stability and product retention.
- Assembly — Numerically calibrated grooved posts, tapered plastic split sleeves and shelf collars combine to make shelving assembly a simple two-step exercise: 1) snap the split sleeves onto a post over the number of your choice; and 2) slide a shelf collar over the split sleeves. A positive lock between shelf and post is created without the use of any tools.
- Open-wire construction promotes higher visibility, allows light to pass through the shelves, permits greater air circulation which helps reduce moisture and dust build-up, and increases the effectiveness of fire-suppression systems.
- Tapered split sleeves of high-temperature-resistant ABS plastic create a positive lock that becomes stronger as the load increases.
- Posts are numbered in increments of 1″ (25mm) to ensure fast and level assembly.
- Leveling feet are provided to help compensate for uneven floor surfaces.
- The mat on an Eagle shelf utilizes a pincer-type design with the mat wire sandwiched between the two top truss wires, adding significant strength and distributing the entire load without stress and strain on the welds.
- Finishes available include EAGLEbrite® zinc, chrome, Valu-Master® gray epoxy, Valu-Gard® green epoxy, red epoxy, black epoxy, white epoxy, EAGLEgard® green epoxy (now with MICROGARD®*), and stainless steel finish.
- All epoxy finishes are approved for wet or dry applications.
- Custom colors also available – see your Price List for reference.

*** MICROGARD® standard on all EAGLEgard® shelving.**
MICROGARD® is an antimicrobial agent which contains built in protection to retard the growth of a broad range of bacteria, mold and mildew on the surface of the shelves that cause stains, odors and degradation.

Options / Accessories

❑ Ledges ❑ Collar plugs
❑ Dividers ❑ Casters*
❑ Shelf markers ❑ Caster posts*

* Accessories to Starter Units only.

Certifications / Approvals

NSF

AutoQuotes
KCL

EAGLE GROUP
100 Industrial Boulevard, Clayton, DE 19938-8903 USA
Phone: 302-653-3000 • Fax: 302-653-2065
www.eaglegrp.com

Foodservice Division: Phone 800-441-8440
MHC/Retail Display Divisions: Phone 800-637-5100

For custom configuration or fabrication needs, contact our **SpecFAB® Division.**
Phone: 302-653-3000 • Fax: 302-653-3091 • e-mail: specfab@eaglegrp.com

Spec sheets available for viewing, printing or downloading from our online literature library at *www.eaglegrp.com*

Eagle Foodservice Equipment, Eagle MHC, SpecFAB®, and Retail Display are divisions of Eagle Group. ©2008 by the Eagle Group

KaTom Restaurant Supply, Inc.

EAGLE GROUP®
Profit from the Eagle Advantage®

Item No.: _____
Project No.: _____
S.I.S. No.: _____

Wire Shelving Starter Units and Add-On Units

To specify finish, add suffix (listed at right) to model number. Example: A4-74-1824**C**

"**Z**" (EAGLEbrite® zinc)
"**C**" (chrome)
"**V**" (Valu-Master® gray epoxy)
"**E**" (EAGLEgard® green epoxy with MICROGARD®)
"**VG**" (Valu-Gard® green epoxy)
"**R**" (red epoxy)
"**BL**" (black epoxy)
"**W**" (white epoxy)
"**S**" (stainless steel)

Starter Units

- Comes with four or five wire shelves and four posts.
- Four-shelf units available in 63˝ and 74˝ (1600 and 1880mm) post heights.
- Five-shelf units available in 74˝ and 86˝ (1880 and 2184mm) post heights.
- Shipped knocked-down.
- 54˝ (1372mm) shelves available.

Four-Shelf Units						Five-Shelf Units									
Models with 63˝ (1600mm) Posts			Models with 74˝ (1880mm) Posts			Models with 74˝ (1880mm) Posts			Models with 86˝ (2184mm) Posts						
	weight			weight			weight			weight		width		length	
model #	lbs.	kg	model #	lbs.	kg	model #	lbs.	kg	model #	lbs.	kg	in.	mm	in.	mm
S4-63-1824	42	19	S4-74-1824	51	23	S5-74-1824	51	23	S5-86-1824	55	25	18˝	457	24˝	610
S4-63-1830	47	21	S4-74-1830	58	26	S5-74-1830	58	26	S5-86-1830	60	27	18˝	457	30˝	762
S4-63-1836	53	24	S4-74-1836	65	30	S5-74-1836	65	30	S5-86-1836	65	30	18˝	457	36˝	914
S4-63-1842	57	26	S4-74-1842	70	32	S5-74-1842	70	32	S5-86-1842	75	34	18˝	457	42˝	1067
S4-63-1848	63	29	S4-74-1848	78	36	S5-74-1848	78	36	S5-86-1848	80	36	18˝	457	48˝	1219
S4-63-1860	82	37	S4-74-1860	102	46	S5-74-1860	102	46	S5-86-1860	105	48	18˝	457	60˝	1524
S4-63-1872	94	43	S4-74-1872	117	53	S5-74-1872	117	53	S5-86-1872	120	54	18˝	457	72˝	1829
S4-63-2124	46	21	S4-74-2124	57	26	S5-74-2124	57	26	S5-86-2124	60	27	21˝	533	24˝	610
S4-63-2130	52	24	S4-74-2130	64	29	S5-74-2130	64	29	S5-86-2130	65	30	21˝	533	30˝	762
S4-63-2136	59	27	S4-74-2136	73	33	S5-74-2136	73	33	S5-86-2136	75	34	21˝	533	36˝	914
S4-63-2142	65	30	S4-74-2142	81	37	S5-74-2142	81	37	S5-86-2142	80	36	21˝	533	42˝	1067
S4-63-2148	71	32	S4-74-2148	88	40	S5-74-2148	88	40	S5-86-2148	90	41	21˝	533	48˝	1219
S4-63-2160	88	40	S4-74-2160	109	50	S5-74-2160	109	50	S5-86-2160	110	50	21˝	533	60˝	1524
S4-63-2172	98	45	S4-74-2172	122	55	S5-74-2172	122	55	S5-86-2172	140	64	21˝	533	72˝	1829
S4-63-2424	50	23	S4-74-2424	62	28	S5-74-2424	62	28	S5-86-2424	65	30	24˝	610	24˝	610
S4-63-2430	57	26	S4-74-2430	71	32	S5-74-2430	71	32	S5-86-2430	75	34	24˝	610	30˝	762
S4-63-2436	65	30	S4-74-2436	81	37	S5-74-2436	81	37	S5-86-2436	85	39	24˝	610	36˝	914
S4-63-2442	72	33	S4-74-2442	89	40	S5-74-2442	89	40	S5-86-2442	95	43	24˝	610	42˝	1067
S4-63-2448	79	36	S4-74-2448	98	45	S5-74-2448	98	45	S5-86-2448	100	45	24˝	610	48˝	1249
S4-63-2460	98	45	S4-74-2460	122	55	S5-74-2460	122	55	S5-86-2460	125	57	24˝	610	60˝	1524
S4-63-2472	120	55	S4-74-2472	149	68	S5-74-2472	149	68	S5-86-2472	150	68	24˝	610	72˝	1829

Add-On Units

- Comes with four or five wire shelves, two posts and two "S" hooks per shelf.
- Four-shelf units available in 63˝ and 74˝ (1600 and 1880mm) post heights.
- Five-shelf units available in 74˝ and 86˝ (1880 and 2184mm) post heights.
- Shipped knocked-down.
- 54˝ (1372mm) shelves available.

Four-Shelf Units						Five-Shelf Units									
Models with 63˝ (1600mm) Posts			Models with 74˝ (1880mm) Posts			Models with 74˝ (1880mm) Posts			Models with 86˝ (2184mm) Posts						
	weight			weight			weight			weight		width		length	
model #	lbs.	kg	model #	lbs.	kg	model #	lbs.	kg	model #	lbs.	kg	in.	mm	in.	mm
A4-63-1824	35	16	A4-74-1824	43	20	A5-74-1824	43	20	A5-86-1824	45	20	18˝	457	24˝	610
A4-63-1830	40	18	A4-74-1830	50	23	A5-74-1830	50	23	A5-86-1830	51	23	18˝	457	30˝	762
A4-63-1836	46	21	A4-74-1836	57	26	A5-74-1836	57	26	A5-86-1836	56	25	18˝	457	36˝	914
A4-63-1842	50	23	A4-74-1842	62	28	A5-74-1842	62	28	A5-86-1842	66	30	18˝	457	42˝	1067
A4-63-1848	56	25	A4-74-1848	70	32	A5-74-1848	70	32	A5-86-1848	71	32	18˝	457	48˝	1219
A4-63-1860	75	34	A4-74-1860	93	42	A5-74-1860	93	42	A5-86-1860	96	44	18˝	457	60˝	1524
A4-63-1872	87	40	A4-74-1872	108	49	A5-74-1872	108	49	A5-86-1872	111	50	18˝	457	72˝	1829
A4-63-2124	39	18	A4-74-2124	48	22	A5-74-2124	48	22	A5-86-2124	51	23	21˝	533	24˝	610
A4-63-2130	45	21	A4-74-2130	56	26	A5-74-2130	56	26	A5-86-2130	56	25	21˝	533	30˝	762
A4-63-2136	52	24	A4-74-2136	65	30	A5-74-2136	65	30	A5-86-2136	66	30	21˝	533	36˝	914
A4-63-2142	58	26	A4-74-2142	73	33	A5-74-2142	73	33	A5-86-2142	71	32	21˝	533	42˝	1067
A4-63-2148	64	29	A4-74-2148	80	36	A5-74-2148	80	36	A5-86-2148	81	37	21˝	533	48˝	1219
A4-63-2160	81	37	A4-74-2160	101	46	A5-74-2160	101	46	A5-86-2160	101	46	21˝	533	60˝	1524
A4-63-2172	92	42	A4-74-2172	113	51	A5-74-2172	113	51	A5-86-2172	131	59	21˝	533	72˝	1829
A4-63-2424	43	20	A4-74-2424	53	24	A5-74-2424	53	24	A5-86-2424	56	25	24˝	610	24˝	610
A4-63-2430	50	23	A4-74-2430	62	28	A5-74-2430	62	28	A5-86-2430	66	30	24˝	610	30˝	762
A4-63-2436	58	36	A4-74-2436	73	33	A5-74-2436	73	33	A5-86-2436	76	35	24˝	610	36˝	914
A4-63-2442	65	30	A4-74-2442	81	37	A5-74-2442	81	37	A5-86-2442	86	39	24˝	610	42˝	1067
A4-63-2448	72	33	A4-74-2448	90	41	A5-74-2448	90	41	A5-86-2448	91	41	24˝	610	48˝	1249
A4-63-2460	91	41	A4-74-2460	113	51	A5-74-2460	113	51	A5-86-2460	116	53	24˝	610	60˝	1524
A4-63-2472	113	51	A4-74-2472	141	64	A5-74-2472	141	64	A5-86-2472	141	64	24˝	610	72˝	1829

EAGLE GROUP
100 Industrial Boulevard, Clayton, DE 19938-8903 USA
Phone: 302-653-3000 • Fax: 302-653-2065
www.eaglegrp.com

Foodservice Division: Phone 800-441-8440
MHC/Retail Display Divisions: Phone 800-637-5100

Printed in U.S.A.
©2008 by Eagle Group
Rev. 09/08

Spec sheets available for viewing, printing or downloading from our online literature library at *www.eaglegrp.com*

Although every attempt has been made to ensure the accuracy of the information provided, we cannot be held responsible for typographical or printing errors. Information and specifications are subject to change without notice. Please confirm at time of order.

KaTom Restaurant Supply, Inc.