

TAYLOR[®]

TE22 Digital Scale



- Capacity: 22lbs/10kg.
- Weight Increments:
1 lb - 11lb. x 0.1oz
11lb - 22lb. x 0.2oz
0kg - 5kg x 2g
5kg - 10kg x 5g
- Platform: 4 1/2 x 6"
- Removeable Stainless Steel Platform.
- Field Recalibratable
- Auto & Manual Shut Off.
- Tare & Hold
- Overload Protection.
- 9V battery and AC adaptor included.

Taylor Precision Products Customer Service:
800-225-4834
www.taylorusa.com



9517L HACCP Infrared Thermometer

This infrared thermometer measures surface temperatures, without contact. Includes a HACCP check light warning system. The compact design allows you to carry it in a pocket or on a belt. Laser site, "Min/Max" and "Hold" features, F & C selectable, CE certified, NIST traceable, Auto shut-off extends battery life, Operating range: 32F to 122F/ 0C to 50C, Resolution: 0.1F or 0.1C. IR specifications: Range: -67/662F; -55/350C,

Accuracy: + 1.8F/ + 1.0C in HACCP Temperature Ranges, Distance to Spot Ratio: 6:1, Adjustable emissivity: 0.1 -1 Step 0.1, Low battery Indicator (includes 2 "AAA" 1.5v batteries), One year limited warranty.

9521 Infrared Thermometer

This infrared thermometer measures surface temperatures, without contact. The compact design of it allows you to carry it in your pocket or on your belt. Laser site, "Max" and "Hold" features, F & C selectable, CE certified, NIST traceable, Auto shut-off extends battery life, Operating range: 32 F to 122 F/ 0 C to 50 C, Resolution: 0.1 F or 0.1 C, Response Time: 1 second. IR



Specifications: Range: -58 F/52 F; -50 C/400 C, Accuracy: + 1.8F/ + 1.0C in HACCP Temperature Ranges, Distance to Spot Ratio: 9:1, Emissivity: 0.95 fixed. Low battery indicator (includes 2 "AAA" 1.5v batteries), Includes vinyl carrying case w/ belt loop, One year limited warranty.

9306 HACCP Dual Temp Thermometer

Waterproof combination infrared and thermocouple thermometer for use in HACCP temperature management programs. Includes HACCP check light warning system. Accuracy + 2F/1C in HACCP temperature ranges. Features include step down thermocouple probe for quick response time; Waterproof rated IP65; Min/Max and hold features; F



& C selectable; Auto off extends battery life; vinyl belt loop case included. CE certified and NIST Traceable.

Model 9848

Antimicrobial Case & Sleeve, Waterproof, Hold Button, Field Recalibratable, Rugged Shock Resistant Case, NSF Listed, F & C selectable, On/Off switch with auto shut off, Thermistor located in probe tip, Dishwasher Safe, Maximum Temperature Memory, One year limited warranty. Specifications: Range: -40 F/450 F (-40 C/230 C), Resolution: 0.1 F or C up to 199.9 (above 1 degree F/C), Accuracy: +/- 1 degree F in HACCP, temperature ranges, Auto Shut-off: After 10 minutes if no change in temperature, Response Time: 5 seconds, Update Time: 2 seconds.



Taylor Precision Products Customer Service:
800-225-4834
www.taylorusa.com



Timestrips®

A disposable, single use "visual alarm clock". Each strip contains a bubble of time and temperature sensitive fluid. Squeeze the bubble to activate the fluid, and the purple color band advances over time to indicate when food has expired and should be discarded. The adhesive backing can be applied directly on packages. The Timestrips® are a simple, convenient way to monitor food freshness. Perfect for use on costly, perishable items. Available in 3, 5, and 7 day strips. 50 strips per box.

- 8803** 3 day Timestrip®
- 8805** 5 day Timestrip®
- 8807** 7 day Timestrip®

8750

180°F/82°C TempRite® Adhesive Dishwasher Temperature Test Labels. Waterproof. One time use. Accuracy +/- 2 degrees F. 1 pack of 24 labels.



Model 9842

Antimicrobial Case & Sleeve, Waterproof, Hold Button, Field Recalibratable, Rugged Shock Resistant Case, NSF Listed, F & C selectable, On/Off switch with auto



shut off, Thermistor located in probe tip, One year limited warranty, Maximum Temperature Memory, One year limited warranty. Specifications: Range: -40 F/450 F (-40 C/230 C), Resolution: 0.1 F or C up to 199.9, (above 1 degree F/C), Accuracy: +/- 1 degree F in HACCP temperature ranges, Auto Shut-off: After 10 minutes if no change in temperature, Response Time: 5 seconds, Update Time: 2 seconds.

330 MULTI-TIMER W/ CLOCK

4 timing modes plus 12 / 24 hour clock, large display, loud alarm, 99 hour 99 minute 59 second timer duration, self standing / magnetic, mounting feature, 4 timing modes color: white / blue / grey 1 year warranty

