

JOB _____ ITEM # _____ QTY # _____



SILVERWARE IN CYLINDERS

MODEL 716-1-A6

Shown with optional silverware cylinders and rotating bumpers.

SPECIFICATIONS

Model 716-1-A6 tray and silverware cart for silverware in cylinders.

FRAME: The frame is constructed of 1" O.D. 16ga. stainless steel tubing with the A6 acting as an integral cross braces welded across the top for rigidity.

SHELVES: Each shelf is press formed from a single sheet of 18 ga. stainless steel. It is flanged down 1-5/16" on all four sides and formed back at a 30° angle for rigidity. Each inside corner is fitted with an ABS black plastic bracket and sleeve to accommodate an upright. The bottom shelf on all models is set 8" above the floor.

SILVERWARE DISPENSER: The dispenser is constructed of 18 ga. stainless steel and is securely welded to the top of the cart. The top is canted and has six round openings to accommodate plastic or stainless steel silverware cylinders.

CASTERS: The unit is mounted on four 4" diameter heavy duty, swivel casters.

OPTIONS

- 159-2701 - Silverware Cylinder, plastic (each)
- 011-3842 - Silverware Cylinder, stainless steel (each)
- 341-3483 - Napkin Dispenser, folded napkin 3-1/2" x 7"
- Y4 - Polyurethane 4" casters (set of 4)
- Y5 - Polyurethane 5" casters (set of 4)
- R - Rotating bumpers
- WB - Two locking casters
- I (for carts) - Silverware, identity plates, stainless steel (knives, forks, t-spoons)

CAPACITY: Approximately 75-150, 14" x 18" trays and 210 to 240 pieces of silverware.

OVERALL DIMENSIONS: 18" long, 21 3/8" wide, 45" high.

Shipping weight: 60

LIMITED WARRANTY: PIPER PRODUCTS warrants to the original purchaser parts and labor for a period of twelve (12) months from the date of purchase. See manufacturer's complete warranty for details.

It is our policy to build equipment which is design certified by companies that have been accredited at the Federal Level by the Occupational Safety and Health Agency (OSHA) and ANSI as a National Recognized Testing Laboratory. These companies include CSA International, Underwriters Laboratories, and the National Sanitation Foundation. However, a continuing program of product improvement makes it necessary to submit new models to the agencies as they are developed. Consequently, all models may not bear the appropriate labels at all times.

We reserve the right to change specifications and product design without notice. Such revisions do not entitle buyer to corresponding changes, improvements, additions or replacements for previously purchased equipment. Information is not for design purposes.

FOR TRAYS, RACKS, TRANSPORTING, BUSSING

MODEL 715-3
Cart shown with optional rotating bumpers.



SPECIFICATIONS

Model 715 series multi-purpose carts.

FRAME: The frame is constructed of 1" O.D. 16 ga. stainless steel tubing formed to serve as push handles at both ends.

SHELVES: Each shelf is press formed from a single sheet of 18 ga. stainless steel. It is flanged down 1-5/16" on all four sides and formed back at a 30° angle for rigidity. Each inside corner is fitted with an ABS black plastic bracket and sleeve to accommodate an upright. The bottom shelf on all models is set 8" above the floor.

CASTERS: The unit is mounted on four 4" diameter heavy duty, swivel casters.

MODELS 715-2 through 715-5: All carts are the same size and construction. The model number suffix indicates number of shelves.

OPTIONS

- Y4 - Polyurethane 4" casters (set of 4)
- Y5 - Polyurethane 5" casters (set of 4)
- R - Rotating bumpers

| MODEL NO. | LENGTH | WIDTH | HEIGHT | NO. OF SHELVES | CLEARANCE BETWEEN SHELVES | SHIPPING WEIGHT |
|--------------------------------|--------|---------|--------|----------------|---------------------------|-----------------|
| <input type="checkbox"/> 715-2 | 36" | 21-3/8" | 36" | 2 | 22-3/4" | 65 |
| <input type="checkbox"/> 715-3 | 36" | 21-3/8" | 36" | 3 | 10-3/4" | 75 |
| <input type="checkbox"/> 715-4 | 36" | 21-3/8" | 45" | 4 | 9-3/4" | 100 |
| <input type="checkbox"/> 715-5 | 36" | 21-3/8" | 45" | 5 | 7" | 120 |

CAPACITY: Two stacks of trays or dish boxes, 15-1/4" x 20-1/2" maximum size - or one stack of racks, 20" x 20" maximum size on each shelf; or suitable combination. Add 3" to overall length and width for rotating bumpers.

SPEC E-9

PIPER PRODUCTS
BUILT TO LAST
www.piperonline.net

300 S. 84th Avenue
Wausau, WI 54401
Phone: 800-544-3057
Fax: 715-842-3125