

RESTAURANT SERIES ELECTRIC BAKERY DEPTH CONVECTION OVENS

SERIES: BPCV-E



Bakers Pride® BPCV-E series convection ovens feature single and double-stacked models with electric operation. These ovens feature a patented two-speed, wheel-within-a-wheel fan that enhances air flow for consistent cooking. The independent doors are fully insulated and feature cool-touch handles. This model is serviceable from the front and includes stainless steel front, top, sides, and doors. The lighted oven chamber has a porcelain enamel interior for easy maintenance and will accept five 18" x 26" sheet pans. Standard rotary controls are simple to use and include a cool-down function and continuous-ring timer.



FEATURES AT A GLANCE

- 10.5 kW forced-air system
- 208 V or 240 V, 60 Hz, single or three phase
- Elements-on and temperatureready indicator lights
- · Electronic temperature control
- Stainless steel front, top, and sides
- 50/50 split independent doors
- Double-pane, thermal glass door windows
- Interior oven light
- · 60-minute, continuous-ring timer
- 150-550°F (65-287°C) temperature range
- Durable two-speed, 1/2 hp fan motor with cool-down mode
- · Porcelain enamel oven interior
- Eleven-position removable rack guides
- Five heavy-duty, chrome-plated wire racks with stop

- Accepts five 18" x 26" (457 x 660 mm) sheet pans (left or right or front to back)
- · One-year limited warranty

OPTIONS & ACCESSORIES

- Solid doors
- Oven racks
- · Stacking kit with casters
- · Stacking kit with legs
- 26" (660 mm) legs with casters
- 26" legs (single unit only)
- 26" stainless steel legs, shelf and rack guides
- 26" stainless steel legs with casters, shelf and rack guides










RESTAURANT SERIES ELECTRIC BAKERY DEPTH CONVECTION OVENS SERIES: BPCV-E

EQUIPMENT DIMENSIONS







Side View

MECHANICAL SPECIFICATIONS

| Model # | Electrical Requirements | Overall Dimensions (W x H x D)** | Interior Dimensions (W x D)* | Carton Dim (W x H x D) | Cubic Feet | Cubic Meter | Ship Wt. |
|---------|---|--|---------------------------------|---------------------------|---------------|----------------|-----------------|
| BPCV-E1 | 208V, 1ph, 53A / 208V, 3ph, 30A, 60hz Two speed motor 1/2 h.p. 1725/1140 | 40" x 62" x 42.62" (1016 x 1575 x 1083) | 26.62" x 26.5" (676 x 673) | | | | 514 (233kg) |
| BPCV-E2 | RPM 240V, 1ph, 46A / 240V, 3ph, 26.5A, 60hz | 40" x 74.5" x 42.62" (1016 x 1892 x 1083) | 26.62" x 26.5" (676 x 673) | | | | 1028 (466kg) |

^{*}Includes rack supports

REQUIRED CLEARANCES

Combustible
Left 10" (254 mm)
Right 10" (254 mm)
Back 4" (254 mm)

Bakers Pride Oven Company, LLC is a wholly owned subsidiary of Standex International Corporation.

Bakers Pride reserves the right to modify specifications or discontinue models without incurring obligation. Dimensions nominal.





Freight Class: 110 FOB: Allen, 75013





^{**}Height includes legs