



O8631V UNIVERSAL ADJUSTABLE TRAY RACK

for 12"x20" Pans and 18"x26" Trays

CARTER-HOFFMANN
11
ADJUSTABLE PAN RACK
FOOD SERVICE EQUIPMENT



O8631V

Model Number	Tray Capacity ¹		Tray Slide Spacing*		Overall Dimensions			Caster Diameter		Shipping Weight		
	18"x26"	12"x20"	in	mm	Height	Depth	Width	in	mm	lbs	kgs	
<input type="checkbox"/> O8631V	12	24	4 1/2	114	64	1626	26	660	24	622	86	39

*adjustable on 1-1/2" increments

¹see below for additional tray/pan types

CONSTRUCTION...Heavy gauge aluminum, fully reinforced with horizontal stabilizing bar to prevent buckling. Top, bottom and corner reinforcements are welded to upright channels which are, in turn, welded to the base frame. Entire base frame and bolster pads are welded to form a solid one piece unit.

CABINET MATERIAL...Extruded tube 1-1/4" x 1-1/2" with 16/15" leg x .070 wall thickness on tube and .125 on leg. Upright leg is notched on 1-1/2" centers to accept universal stepped tray slide.

ANGLE SLIDES... stepped type; 2" x 6-3/16" x .100 thick. Bottom guides welded in place for support. Removable and adjustable on 1-1/2" centers. Standard spacing at 4-1/2" centers. Accommodate a wide variety of trays and pans, from 20" in width to 26" in length, including:
 10"x20" roast and bake pans
 20"x22" roast and bake pans
 18"x26" roasting pans
 18"x26" bun pans
 12"x20" steam table pans
 1/1 gastronorm pans
 2/1 gastronorm pans
 15"x20" service trays
 20"x20" glass racks

CASTERS...Four 5" platform type swivel casters.

ACCESSORIES/OPTIONS...

- Caster locks (2)
- Corner bumpers (4)
- Pan stop
- Perimeter bumper
- Vertical bumpers

SPECIFICATIONS

Specifications subject to change through product improvement & innovation.

CARTER-HOFFMANN
 1551 McCormick Ave., Mundelein, IL 60060
 (847) 362-5500 • (800) 323-9793 • Fax (847) 367-8981
www.carter-hoffmann.com

KaTom Restaurant Supply, Inc.

Printed in U.S.A. J35 0609
 Carter-Hoffmann is a trademark
 of Carter-Hoffmann LLC



O1838C LIP LOADED BUN PAN RACK for 18" x 26" Trays



Model Number	Tray Capacity ¹ 18"x26"	Tray Slide Spacing		Overall Dimensions			Caster Diameter		Shipping Weight	
		in	mm	Height	Depth	Width	in	mm	lbs	kg
O1838C	38	1 1/2	38	69 3/4 1772	26 660	20 3/8 517	5	127	56	25

¹lip-loaded

CONSTRUCTION...All welded, heavy-duty, high tensile, type 6463-T5 alloy extruded aluminum. Fully reinforced with horizontal stabilizing bars to prevent buckling.

CABINET MATERIAL... Vertical and horizontal frame members are 1" x 1" x .070 extruded aluminum tubing. Corner gussets of 1-1/2" x 1-1/2" x 5/8" thick angle are welded to the inside angles (bottom side) where horizontal cross bracing meets vertical uprights.

CHANNEL SLIDES... Slides are 3/4" x 1-9/16" channel slides welded to frame. Accept 18"x26" lip loaded bun pans on 1-1/2" centers.

CASTERS... Four 5" diameter platform casters. All swivel with sealed ball bearing. Non-marking polyurethane.

ACCESSORIES/OPTIONS...

- Solid base
- Corner bumpers (4)
- Caster locks (2) for 5" platform casters
- Perimeter bumper
- Pan stop
- Vertical bumpers

CARTER-HOFFMANN
 11
 FOOD SERVICE EQUIPMENT
 LIP LOADED BUN PAN RACK

SPECIFICATIONS

Specifications subject to change through product improvement & innovation.

CARTER-HOFFMANN
 1551 McCormick Ave., Mundelein, IL 60060
 (847) 362-5500 • (800) 323-9793 • Fax (847) 367-8981
www.carter-hoffmann.com

KaTom Restaurant Supply, Inc.

Printed in U.S.A. J35 0609
 Carter-Hoffmann is a trademark
 of Carter-Hoffmann LLC