

GLASS DOOR MERCHANDISERS



FLORAL CASES

MODEL	DOORS	Cu. Ft.	# OF SHELVES	HP	AMPS	CRATED WEIGHT	CABINET DIMENSIONS L D† H		
GDM-12FC	1 swing	12	2	1/5	5.0	233	24 ^{7/8} x 23 x 62 ^{3/8}		
GDM-23FC	1 swing	23	2	1/3	7.2	295	27 x 29 ^{1/2} x 78 ^{1/4}		
GDM-23FC-RF	1 swing	23	2	1/3	7.2	310	27 x 31 ^{1/4} x 78 ^{1/4}		
GDM-47FC	2 slide	47	4	1/2	10.3	425	54 x 29 ^{1/2} x 78 ^{1/4}		
GDM-49FC	2 swing	49	4	1/2	7.2	465	54 x 29 ^{1/2} x 78 ^{1/4}		
GDM-61FC	2 slide	61	4	1/2	11.3	594	70 x 29 ^{1/2} x 79 ^{1/4}		
GDM-69FC	3 slide	69	6	1/2	12.0	610	78 ^{1/4} x 29 ^{1/2} x 79 ^{1/4}		
GDM-72FC	3 swing	72	6	1/2	12.0	630	78 ^{1/4} x 29 ^{1/2} x 79 ^{1/4}		

White and rosewood vinyl exterior available at no extra charge.

† Depth does not include 1^{3/8}" for handle on swing door models (excludes -RF model); or 3/8" for slide door models.

† Depth does not include 1" for rear bumpers on GDM-12FC.

GLASS END FLORAL CASES

MODEL	DOORS	Cu. Ft.	# OF SHELVES	HP	AMPS	CRATED WEIGHT	CABINET DIMENSIONS L D† H		
GEM-12FC	1 swing	12	2	1/5	5.0	250	24 ^{7/8} x 23 x 62 ^{3/8}		
GEM-23FC	1 swing	23	2	1/3	7.2	350	27 x 29 ^{1/2} x 78 ^{1/4}		
G4SM-23FC	1 swing	23	2	1/2	10.0	416	27 x 29 ^{3/4} x 78 ^{1/4}		
GEM-47FC	2 slide	47	4	1/2	10.3	540	54 x 29 ^{1/2} x 78 ^{1/4}		
GEM-69FC	3 slide	69	6	1/2	12.0	704	78 ^{1/4} x 29 ^{1/2} x 79 ^{1/4}		
GEM-72FC	3 swing	72	6	1/2	12.0	718	78 ^{1/4} x 29 ^{1/2} x 79 ^{1/4}		

White and rosewood vinyl exterior available at no extra charge.

† Depth does not include 1^{3/8}" for handle on swing door models, or 3/8" for slide door models.

† Depth does not include 1" for rear bumpers on GEM-12FC.

WINE MERCHANDISER

MODEL	SWING DOORS	Cu. Ft.	SHELVES WIRE WINE		HP	AMPS	CRATED WEIGHT	CABINET DIMENSIONS L D† H		
GDM-23W	1	23	1	4	1/3	7.2	305	27 x 29 ^{1/2} x 78 ^{1/4}		

White and rosewood vinyl exterior available at no extra charge.

† Depth does not include 1^{3/8}" for door handle.

note: wine merchandiser standard with four wire wine racks and one wire shelf per door.

RADIUS FRONT WINE MERCHANDISERS

MODEL	SWING DOORS	Cu. Ft.	SHELVES WIRE WINE		HP	AMPS	CRATED WEIGHT	CABINET DIMENSIONS L D† H		
GDM-23W-RF	1	23	1	4	1/3	7.2	315	27 x 31 ^{1/4} x 78 ^{1/4}		
GDM-49W-RF	2	49	2	8	1/2	7.2	440	54 ^{1/8} x 34 ^{3/4} x 78 ^{1/4}		

White and rosewood vinyl exterior available at no extra charge.

† Depth does not include 1^{3/8}" for door handle on two door models.

note: wine merchandisers standard with four wire wine racks and one wire shelf per door.



GDM-49FC



GDM-23W-RF

FEATURES/BENEFITS

- Oversized, environmentally friendly (134A) refrigeration system.
- Exterior durable and permanent non-peel or chip black laminated vinyl (white and rosewood vinyl available at no extra charge).
G4SM model standard in copper aluminum finish.
- Interior - attractive NSF approved, black aluminum for vivid contrast and dramatic display of flowers. Non peel or chip interior - will last a lifetime. 300 series stainless steel floor.
- Energy efficient, "Low-E", thermal glass.
- Illuminated sign panel. (decal on 12FC models).
- Adjustable, heavy duty, black PVC coated wire shelves.
- Safety shielded, low UV emitting fluorescent interior lighting.
- Foamed-in-place polyurethane high density cell insulation (CFC Free).
- Positive seal self-closing doors.
- Self-contained system, no plumbing required.
- Bottom mount compressor.
- Energy efficient.
- Available with optional legs or 2^{1/2}" diameter castors.
- GDM-12FC and GEM-12FC available with optional 2^{1/2}" diameter castors only.
- See our website www.truemfg.com for the latest color & sign offerings.
- Mirrored interior backs available. Upcharge and lead times will apply.

Wine Merchandiser Units...

- Designed to hold 33°F to 38°F.
- Standard with 4 wine racks and 1 wire shelf per door.
- Standard with mirrored back.
- GDM-23W and GDM-23W-RF are standard with locks.
- Optional red wine, chocolate, or white wine thermostat available.

Remote cabinets available 14% off list (condensing units supplied by others; system comes standard with 404A expansion valve and requires R404A refrigerant). Consult factory technical service dept. for BTU information.