

## REACH-IN GLASS DOOR REFRIGERATORS



TA1R-2HG

MODEL	SWING DOORS	CU. FT.	HP	AMPS	CRATED WEIGHT	CABINET DIMENSIONS L D† H*
<b>GLASS DOORS</b>						
TA1R-1G	1	31	1/3	9.0	410	29 x 34 <sup>7</sup> / <sub>8</sub> x 78 <sup>1</sup> / <sub>4</sub>
TA2R-2G	2	56	1/2	11.4	710	51 <sup>3</sup> / <sub>8</sub> x 34 <sup>7</sup> / <sub>8</sub> x 78 <sup>1</sup> / <sub>4</sub>
TA3R-3G	3	85	3/4	13.6	867	76 <sup>1</sup> / <sub>2</sub> x 34 <sup>7</sup> / <sub>8</sub> x 78 <sup>1</sup> / <sub>4</sub>
<b>GLASS HALF DOORS</b>						
TA1R-2HG	2	31	1/3	9.0	465	29 x 34 <sup>7</sup> / <sub>8</sub> x 78 <sup>1</sup> / <sub>4</sub>
TA2R-4HG	4	56	1/2	11.4	660	51 <sup>3</sup> / <sub>8</sub> x 34 <sup>7</sup> / <sub>8</sub> x 78 <sup>1</sup> / <sub>4</sub>
<b>COMBINATION HALF DOORS</b>						
TA1R-1HG/1HS	2	31	1/3	9.0	465	29 x 34 <sup>7</sup> / <sub>8</sub> x 78 <sup>1</sup> / <sub>4</sub>
TA2R-2HG/2HS	4	56	1/2	10.0	640	51 <sup>3</sup> / <sub>8</sub> x 34 <sup>7</sup> / <sub>8</sub> x 78 <sup>1</sup> / <sub>4</sub>

† Depth does not include 1<sup>3</sup>/<sub>8</sub>" for door handle (glass door models only).

\* Height does not include 5" for castor height or 6" for optional legs.

\* Height does not include 1" for system mechanical components.



TA2R-2HG/2HS

*Cabinets shown with various tray slide options*

### FEATURES/BENEFITS

- Shelving - (3) heavy duty, PVC coated wire shelves per section (4) different interior kits available. See "spec. series" accessory pages 70 or 134 for details (field installation required).
- Oversized and balanced, environmentally friendly, refrigeration system, factory sealed and pre-lubricated for long life.
- Food safe refrigerators hold 33°F to 38°F.
- Fluorescent interior lighting.
- Exterior - 300 series stainless steel front, sides, bottom and back (the finest stainless available).
- Interior - attractive, NSF approved, white aluminum sides and back. 300 series stainless floor and solid door liner.
- Positive seal self-closing doors with 120 degree stay open feature (center door of 3 section model has 90 degree stay open feature). Lifetime guaranteed door hinges.
- Foamed-in-place polyurethane high density cell insulation (CFC free).
- Energy efficient, "Low-E", thermal insulated glass on glass doors.
- Exterior, digital temperature display.
- Lifetime guaranteed recessed handles on solid doors.
- Door locks standard.
- Extruded, aluminum door frames on glass doors.
- Top mounted unit positioned out of food zone to maximize storage capacity.
- 4" diameter swivel castors standard equipment. 6" legs available.
- Hot gas condensate for energy efficiency.
- Self-contained system.

Curb mountable units for TR, TA & TG series only. (5% list upcharge)

Remote cabinets available: 14% off list (condensing units supplied by others; system comes standard with 404A expansion valve and requires R404A refrigerant). Consult factory technical service dept. for BTU information.