

PASS-THRU REFRIGERATORS (FRONT & REAR SOLID DOORS)

MODEL	SWING DOORS	CU. FT.	HP	AMPS	CRATED WEIGHT	CABINET DIMENSIONS L D H*
SOLID FRONT/SOLID REAR DOORS						
TA1RPT-1S-1S	2	31	1/2	10.4	370	29 x 37 ¹ / ₄ x 78 ¹ / ₄
TA2RPT-2S-2S	4	56	3/4	15.5	710	51 ³ / ₈ x 37 ¹ / ₄ x 78 ¹ / ₄
SOLID FRONT HALF DOORS/SOLID REAR DOORS						
TA1RPT-2HS-1S	3	31	1/2	10.4	535	29 x 37 ¹ / ₄ x 78 ¹ / ₄
TA2RPT-4HS-2S	6	56	3/4	15.5	N/A	51 ³ / ₈ x 37 ¹ / ₄ x 78 ¹ / ₄

* Height does not include 5" for castor height or 6" for optional legs or 1" for mechanical components.

PASS-THRU REFRIGERATORS (SOLID REAR DOORS)

MODEL	SWING DOORS	CU. FT.	HP	AMPS	CRATED WEIGHT	CABINET DIMENSIONS L D† H*
GLASS FRONT/SOLID REAR DOORS						
TA1RPT-1G-1S	2	31	1/2	10.4	525	29 x 37 ¹ / ₂ x 78 ¹ / ₄
TA2RPT-2G-2S	4	56	3/4	15.5	N/A	51 ³ / ₈ x 37 ¹ / ₂ x 78 ¹ / ₄
GLASS FRONT HALF DOORS/SOLID REAR DOORS						
TA1RPT-2HG-1S	3	31	1/2	10.4	N/A	29 x 37 ¹ / ₂ x 78 ¹ / ₄
TA2RPT-4HG-2S	6	56	3/4	15.5	N/A	51 ³ / ₈ x 37 ¹ / ₂ x 78 ¹ / ₄
COMBINATION FRONT HALF DOORS/SOLID REAR DOORS						
TA1RPT-1HG/1HS-1S	3	31	1/2	10.4	N/A	29 x 37 ¹ / ₂ x 78 ¹ / ₄
TA2RPT-2HG/2HS-2S	6	56	3/4	15.5	N/A	51 ³ / ₈ x 37 ¹ / ₂ x 78 ¹ / ₄

† Depth does not include 1³/₈" for door handles (glass door models only).

* Height does not include 5" for castor height or 6" for optional legs or 1" for mechanical components.

PASS-THRU REFRIGERATORS (GLASS REAR DOORS)

MODEL	SWING DOORS	CU. FT.	HP	AMPS	CRATED WEIGHT	CABINET DIMENSIONS L D† H*
SOLID FRONT/GLASS REAR DOORS						
TA1RPT-1S-1G	2	31	1/2	10.4	525	29 x 37 ¹ / ₂ x 78 ¹ / ₄
TA2RPT-2S-2G	4	56	3/4	15.5	N/A	51 ³ / ₈ x 37 ¹ / ₂ x 78 ¹ / ₄
SOLID FRONT HALF DOORS/GLASS REAR DOORS						
TA1RPT-2HS-1G	3	31	1/2	10.4	N/A	29 x 37 ¹ / ₂ x 78 ¹ / ₄
TA2RPT-4HS-2G	6	56	3/4	15.5	N/A	51 ³ / ₈ x 37 ¹ / ₂ x 78 ¹ / ₄
GLASS FRONT/GLASS REAR DOORS						
TA1RPT-1G-1G	2	31	1/2	10.4	440	29 x 37 ⁵ / ₈ x 78 ¹ / ₄
TA2RPT-2G-2G	4	56	3/4	15.5	740	51 ³ / ₈ x 37 ⁵ / ₈ x 78 ¹ / ₄
GLASS FRONT HALF DOORS/GLASS REAR DOORS						
TA1RPT-2HG-1G	3	31	1/2	10.4	N/A	29 x 37 ⁵ / ₈ x 78 ¹ / ₄
TA2RPT-4HG-2G	6	56	3/4	15.5	N/A	51 ³ / ₈ x 37 ⁵ / ₈ x 78 ¹ / ₄
COMBINATION FRONT HALF DOORS/GLASS REAR DOORS						
TA1RPT-1HG/1HS-1G	3	31	1/2	10.4	N/A	29 x 37 ⁵ / ₈ x 78 ¹ / ₄
TA2RPT-2HG/2HS-2G	6	56	3/4	15.5	N/A	51 ³ / ₈ x 37 ⁵ / ₈ x 78 ¹ / ₄

† Depth does not include 1³/₈" for glass door handles, front or back.

* Height does not include 5" for castor height or 6" for optional legs or 1" for mechanical components.



TA1RPT-1S-1S



TA2RPT-2S-2S

True's TA Series 1 and 2 section pass-thru refrigerators can be built with any combination of half & full doors in both stainless steel and glass. Please contact your local True representative for nomenclature, pricing and lead times.

FEATURES/BENEFITS

- Shelving - (3) heavy duty, PVC coated wire shelves per section (4) different interior kits available. See "spec. series" accessory pages 70 or 134 for details (field installation required).
- Oversized and balanced, environmentally friendly, refrigeration system, factory sealed and pre-lubricated for long life.
- Food safe refrigerators hold 33°F to 38°F.
- Exterior - 300 series stainless steel front, sides, bottom and back (the finest stainless available).
- Interior - attractive, NSF approved, white aluminum sides and back. 300 series stainless floor and solid door liner.
- The utility of the "TA" series pass-thru is in its ability to be a server station for cold dishes. Designed to become a central station, rear-loaded from the kitchen prep area to be front-accessed by servers.
- Foamed-in-place polyurethane high density cell insulation (CFC free).
- Lifetime guaranteed recessed door handles.
- Door locks standard.
- Exterior, digital temperature display.
- Positive seal self-closing doors with 120 degree stay open feature. Lifetime guaranteed door hinges.
- Incandescent interior lighting on solid door models. Fluorescent interior lighting on glass & combo door models.
- Extruded, aluminum door frames on glass doors.
- Energy efficient, "Low-E", thermal insulated glass on glass doors.
- 4" diameter swivel castors standard equipment. 6" legs available.
- Hot gas condensate for energy efficiency.
- Top mounted unit positioned out of food zone to maximize storage capacity.
- Self-contained system.

Curb mountable units for TR, TA & TG series only. (5% list upcharge)

Remote cabinets available 14% off list (condensing units supplied by others; system comes standard with 404A expansion valve and requires R404A refrigerant). Consult factory technical service dept. for BTU information.