

## REACH-IN GLASS DOOR REFRIGERATORS



TR1R-2HG

| MODEL                         | SWING DOORS | CU. Ft. | HP  | AMPS | CRATED WEIGHT | CABINET DIMENSIONS<br>L D† H*  |
|-------------------------------|-------------|---------|-----|------|---------------|--|
| <b>GLASS DOORS</b>            |             |         |     |      |               |  |
| TR1R-1G                       | 1           | 31      | 1/3 | 9.0  | 410           | 29 x 34 <sup>7</sup> / <sub>8</sub> x 78 <sup>1</sup> / <sub>4</sub>                             |
| TR2R-2G                       | 2           | 56      | 1/2 | 11.4 | 710           | 51 <sup>3</sup> / <sub>8</sub> x 34 <sup>7</sup> / <sub>8</sub> x 78 <sup>1</sup> / <sub>4</sub> |
| TR3R-3G                       | 3           | 85      | 3/4 | 13.6 | 867           | 76 <sup>1</sup> / <sub>2</sub> x 34 <sup>7</sup> / <sub>8</sub> x 78 <sup>1</sup> / <sub>4</sub> |
| <b>GLASS HALF DOORS</b>       |             |         |     |      |               |  |
| TR1R-2HG                      | 2           | 31      | 1/3 | 9.0  | 465           | 29 x 34 <sup>7</sup> / <sub>8</sub> x 78 <sup>1</sup> / <sub>4</sub>                             |
| TR2R-4HG                      | 4           | 56      | 1/2 | 11.4 | 660           | 51 <sup>3</sup> / <sub>8</sub> x 34 <sup>7</sup> / <sub>8</sub> x 78 <sup>1</sup> / <sub>4</sub> |
| <b>COMBINATION HALF DOORS</b> |             |         |     |      |               |  |
| TR1R-1HG/1HS                  | 2           | 31      | 1/3 | 9.0  | 465           | 29 x 34 <sup>7</sup> / <sub>8</sub> x 78 <sup>1</sup> / <sub>4</sub>                             |
| TR2R-2HG/2HS                  | 4           | 56      | 1/2 | 10.0 | 640           | 51 <sup>3</sup> / <sub>8</sub> x 34 <sup>7</sup> / <sub>8</sub> x 78 <sup>1</sup> / <sub>4</sub> |

† Depth does not include 1<sup>3</sup>/<sub>8</sub>" for door handle (glass door models only).

\* Height does not include 5" for castor height or 6" for optional legs.

\* Height does not include 1" for system mechanical components.

*True's broad shelving options include four different interior kits.*



TR2R-2HG/2HS



TR3R-3G

### FEATURES/BENEFITS

- Shelving - (1) interior kit option included per full section at no charge. (4) different interior kits available. See "spec. series" accessory pages 70 or 134 for details.
- Pilasters and tray slides/shelving are factory installed at no charge.
- Oversized and balanced, environmentally friendly, refrigeration system, factory sealed and pre-lubricated for long life.
- Food safe refrigerators hold 33°F to 38°F.
- Fluorescent interior lighting.
- Exterior - 300 series stainless steel front, sides, bottom and back (the finest stainless available).
- Interior - 300 series stainless steel walls, back, floor & solid door liner.
- Positive seal self-closing doors with 120 degree stay open feature (center door of 3 section model has 90 degree stay open feature). Lifetime guaranteed door hinges.
- Foamed-in-place polyurethane high density cell insulation (CFC free).
- Energy efficient, "Low-E", thermal insulated glass on glass door models.
- Exterior, digital temperature display.
- Lifetime guaranteed recessed handles on solid doors.
- Door locks standard.
- Extruded, aluminum door frames on glass doors.
- Top mounted unit positioned out of food zone to maximize storage capacity.
- 4" diameter swivel castors standard equipment. 6" legs available.
- Hot gas condensate for energy efficiency.
- Self-contained system.

Curb mountable units for TR, TA & TG series only. (5% list upcharge)

Remote cabinets available 14% off list (condensing units supplied by others; system comes standard with 404A expansion valve and requires R404A refrigerant). Consult factory technical service dept. for BTU information.