

## PASS-THRU REFRIGERATORS (FRONT & REAR SOLID DOORS)

MODEL	SWING DOORS	Cu. Ft.	HP	AMPS	CRATED WEIGHT	CABINET DIMENSIONS		
						L	D	H*
<b>SOLID FRONT/SOLID REAR DOORS</b>								
TR1RPT-1S-1S	2	31	1/2	10.4	370	29	37 <sup>1</sup> / <sub>4</sub>	78 <sup>1</sup> / <sub>4</sub>
TR2RPT-2S-2S	4	56	3/4	15.5	710	51 <sup>3</sup> / <sub>8</sub>	37 <sup>1</sup> / <sub>4</sub>	78 <sup>1</sup> / <sub>4</sub>
<b>SOLID FRONT HALF DOORS/SOLID REAR DOORS</b>								
TR1RPT-2HS-1S	3	31	1/2	10.4	535	29	37 <sup>1</sup> / <sub>4</sub>	78 <sup>1</sup> / <sub>4</sub>
TR2RPT-4HS-2S	6	56	3/4	15.5	N/A	51 <sup>3</sup> / <sub>8</sub>	37 <sup>1</sup> / <sub>4</sub>	78 <sup>1</sup> / <sub>4</sub>

\* Height does not include 5" for castor height or 6" for optional legs or 1" for mechanical components.

## PASS-THRU REFRIGERATORS (SOLID REAR DOORS)

MODEL	SWING DOORS	Cu. Ft.	HP	AMPS	CRATED WEIGHT	CABINET DIMENSIONS		
						L	D†	H*
<b>GLASS FRONT/SOLID REAR DOORS</b>								
TR1RPT-1G-1S	2	31	1/2	10.4	525	29	37 <sup>1</sup> / <sub>2</sub>	78 <sup>1</sup> / <sub>4</sub>
TR2RPT-2G-2S	4	56	3/4	15.5	N/A	51 <sup>3</sup> / <sub>8</sub>	37 <sup>1</sup> / <sub>2</sub>	78 <sup>1</sup> / <sub>4</sub>
<b>GLASS FRONT HALF DOORS/SOLID REAR DOORS</b>								
TR1RPT-2HG-1S	3	31	1/2	10.4	N/A	29	37 <sup>1</sup> / <sub>2</sub>	78 <sup>1</sup> / <sub>4</sub>
TR2RPT-4HG-2S	6	56	3/4	15.5	N/A	51 <sup>3</sup> / <sub>8</sub>	37 <sup>1</sup> / <sub>2</sub>	78 <sup>1</sup> / <sub>4</sub>
<b>COMBINATION FRONT HALF DOORS/SOLID REAR DOORS</b>								
TR1RPT-1HG/1HS-1S	3	31	1/2	10.4	N/A	29	37 <sup>1</sup> / <sub>2</sub>	78 <sup>1</sup> / <sub>4</sub>
TR2RPT-2HG/2HS-2S	6	56	3/4	15.5	N/A	51 <sup>3</sup> / <sub>8</sub>	37 <sup>1</sup> / <sub>2</sub>	78 <sup>1</sup> / <sub>4</sub>

† Depth does not include 1<sup>3</sup>/<sub>8</sub>" for door handles (glass door models only).

\* Height does not include 5" for castor height or 6" for optional legs or 1" for mechanical components.

## PASS-THRU REFRIGERATORS (GLASS REAR DOORS)

MODEL	SWING DOORS	Cu. Ft.	HP	AMPS	CRATED WEIGHT	CABINET DIMENSIONS		
						L	D†	H*
<b>SOLID FRONT/GLASS REAR DOORS</b>								
TR1RPT-1S-1G	2	31	1/2	10.4	525	29	37 <sup>1</sup> / <sub>2</sub>	78 <sup>1</sup> / <sub>4</sub>
TR2RPT-2S-2G	4	56	3/4	15.5	N/A	51 <sup>3</sup> / <sub>8</sub>	37 <sup>1</sup> / <sub>2</sub>	78 <sup>1</sup> / <sub>4</sub>
<b>SOLID FRONT HALF DOORS/GLASS REAR DOORS</b>								
TR1RPT-2HS-1G	3	31	1/2	10.4	N/A	29	37 <sup>1</sup> / <sub>2</sub>	78 <sup>1</sup> / <sub>4</sub>
TR2RPT-4HS-2G	6	56	3/4	15.5	N/A	51 <sup>3</sup> / <sub>8</sub>	37 <sup>1</sup> / <sub>2</sub>	78 <sup>1</sup> / <sub>4</sub>
<b>GLASS FRONT/GLASS REAR DOORS</b>								
TR1RPT-1G-1G	2	31	1/2	10.4	440	29	37 <sup>5</sup> / <sub>8</sub>	78 <sup>1</sup> / <sub>4</sub>
TR2RPT-2G-2G	4	56	3/4	15.5	740	51 <sup>3</sup> / <sub>8</sub>	37 <sup>5</sup> / <sub>8</sub>	78 <sup>1</sup> / <sub>4</sub>
<b>GLASS FRONT HALF DOORS/GLASS REAR DOORS</b>								
TR1RPT-2HG-1G	3	31	1/2	10.4	N/A	29	37 <sup>5</sup> / <sub>8</sub>	78 <sup>1</sup> / <sub>4</sub>
TR2RPT-4HG-2G	6	56	3/4	15.5	N/A	51 <sup>3</sup> / <sub>8</sub>	37 <sup>5</sup> / <sub>8</sub>	78 <sup>1</sup> / <sub>4</sub>
<b>COMBINATION FRONT HALF DOORS/GLASS REAR DOORS</b>								
TR1RPT-1HG/1HS-1G	3	31	1/2	10.4	N/A	29	37 <sup>5</sup> / <sub>8</sub>	78 <sup>1</sup> / <sub>4</sub>
TR2RPT-2HG/2HS-2G	6	56	3/4	15.5	N/A	51 <sup>3</sup> / <sub>8</sub>	37 <sup>5</sup> / <sub>8</sub>	78 <sup>1</sup> / <sub>4</sub>

† Depth does not include 1<sup>3</sup>/<sub>8</sub>" for glass door handles, front or back.

\* Height does not include 5" for castor height or 6" for optional legs or 1" for mechanical components.



TR1RPT-1S-1S



TR2RPT-4HG-2S

True's TR Series 1 and 2 section pass-thru refrigerators can be built with any combination of half & full doors in both stainless steel and glass. Please contact your local True representative for nomenclature, pricing and lead times.

## FEATURES/BENEFITS

- Shelving - (1) interior kit option included per full section at no charge. (4) different interior kits available. See "spec. series" accessory pages 70 or 134 for details.
- Pilasters and tray slides/shelving are factory installed at no charge.
- Oversized and balanced, environmentally friendly, refrigeration system, factory sealed and pre-lubricated for long life.
- Food safe refrigerators hold 33°F to 38°F.
- The utility of the "TR" series pass-thru is in its ability to be a server station for cold dishes. Designed to become a central station, rear-loaded from the kitchen prep area to be front-accessed by servers.
- Exterior - 300 series stainless steel front, sides, bottom and back (the finest stainless available).
- Interior - 300 series stainless steel walls, back, floor & solid door liner.
- Foamed-in-place polyurethane high density cell insulation (CFC free).
- Lifetime guaranteed recessed handles on solid doors.
- Door locks standard.
- Positive seal self-closing doors with 120 degree stay open feature. Lifetime guaranteed door hinges.
- Incandescent interior lighting on solid doors. Fluorescent interior lighting on glass & combo doors.
- Energy efficient, "Low-E", thermal insulated glass on glass doors.
- Extruded, aluminum door frames on glass doors.
- Exterior, digital temperature display.
- 4" diameter swivel castors standard equipment. 6" legs available.
- Hot gas condensate for energy efficiency.
- Top mounted unit positioned out of food zone to maximize storage capacity.
- Self-contained system.

Curb mountable units for TR, TA & TG series only. (5% list upcharge)

Remote cabinets available 14% off list (condensing units supplied by others; system requires R404A refrigerant). Consult factory technical service dept. for BTU information.