

## 300 SERIES STAINLESS STEEL, DEEP REACH-IN REFRIGERATORS

MODEL	GLASS DOORS	SOLID DOORS	CU. FT.	CHROME SHELVES	HP	AMPS	CRATED WEIGHT	CABINET DIMENSIONS L D H*
<b>SOLID DOORS</b>								
TS-28	N/A	1 front	28	3	1/3	7.5	315	29 x 32 <sup>1</sup> / <sub>2</sub> x 78 <sup>3</sup> / <sub>8</sub>
TS-53	N/A	2 front	53	6	1/2	11.8	430	51 <sup>1</sup> / <sub>4</sub> x 32 <sup>1</sup> / <sub>2</sub> x 78 <sup>3</sup> / <sub>8</sub>
<b>SOLID HALF DOORS</b>								
TS-28-2	N/A	2 front	28	3	1/3	7.5	315	29 x 32 <sup>1</sup> / <sub>2</sub> x 78 <sup>3</sup> / <sub>8</sub>
TS-53-4	N/A	4 front	53	6	1/2	11.8	445	51 <sup>1</sup> / <sub>4</sub> x 32 <sup>1</sup> / <sub>2</sub> x 78 <sup>3</sup> / <sub>8</sub>

\* Height does not include 5" for castors or 6" for optional legs.

## 300 SERIES STAINLESS STEEL, DEEP PASS-THRU REFRIGERATORS

MODEL	GLASS DOORS	SOLID DOORS	CU. FT.	CHROME SHELVES	HP	AMPS	CRATED WEIGHT	CABINET DIMENSIONS L D† H*
<b>SOLID FRONT DOORS/SOLID REAR DOORS</b>								
TS-28-PT	N/A	1 front/1 back	28	3	1/2	9.6	390	29 x 35 <sup>1</sup> / <sub>8</sub> x 78 <sup>3</sup> / <sub>8</sub>
TS-53-PT	N/A	2 front/2 back	53	6	1/2	11.8	485	51 <sup>1</sup> / <sub>4</sub> x 35 <sup>1</sup> / <sub>8</sub> x 78 <sup>3</sup> / <sub>8</sub>
<b>SOLID FRONT HALF DOORS/SOLID REAR DOORS</b>								
TS-28-2-PT	N/A	2 front/1 back	28	3	1/2	9.6	415	29 x 35 <sup>1</sup> / <sub>8</sub> x 78 <sup>3</sup> / <sub>8</sub>
TS-53-4-PT	N/A	4 front/2 back	53	6	1/2	11.8	575	51 <sup>1</sup> / <sub>4</sub> x 35 <sup>1</sup> / <sub>8</sub> x 78 <sup>3</sup> / <sub>8</sub>
<b>GLASS FRONT DOORS/SOLID REAR DOORS</b>								
TS-28G-PT	1 front	1 back	28	3	1/2	9.6	385	29 x 35 <sup>1</sup> / <sub>4</sub> x 78 <sup>3</sup> / <sub>8</sub>
TS-53G-PT	2 front	2 back	53	6	1/2	11.8	520	51 <sup>1</sup> / <sub>4</sub> x 35 <sup>1</sup> / <sub>4</sub> x 78 <sup>3</sup> / <sub>8</sub>
<b>GLASS FRONT HALF DOORS/SOLID REAR DOORS</b>								
TS-28-2-G-2-PT	2 front	2 back	28	3	1/2	9.6	430	29 x 35 <sup>1</sup> / <sub>4</sub> x 78 <sup>3</sup> / <sub>8</sub>
TS-53-4-G-4-PT	4 front	4 back	53	6	1/2	11.8	545	51 <sup>1</sup> / <sub>4</sub> x 35 <sup>1</sup> / <sub>4</sub> x 78 <sup>3</sup> / <sub>8</sub>

† Depth does not include 1<sup>3</sup>/<sub>8</sub>" for door handle (glass doors only).

\* Height does not include 5" for castors or 6" for optional legs.



TS-28-2-G-2-PT



TS-28



TS-53-4-G-4-PT

*(glass door models feature optional shelving)*

## FEATURES/BENEFITS

- Oversized and balanced, environmentally friendly (134A), refrigeration system, factory sealed and pre-lubricated for long life - holds 33°F to 38°F.
- The utility of the "TS" series pass-thru is in its ability to be a server station for cold dishes. Designed to become a central station, rear-loaded from the kitchen prep area to be front-accessed by servers.
- Shelving - (3) chrome shelves per section at no charge (includes four knob style shelf supports per shelf (shipped separately). (4) alternative interior options available. See accessory page 134 for details.
- Pilasters and tray slides - are to be field installed for TS series deep reach-in's & pass-thru models. (pilasters and tray slides ship separate)
- Door locks standard.
- Energy efficient, "Low-E", thermal insulated glass on glass door models.
- Lifetime guaranteed recessed door handles on solid rear doors.
- 300 series stainless steel interior and exterior front & sides, with matching aluminum back (stainless steel rear doors on pass-thru models).
- Solar, digital temperature display standard for easy visibility.
- Positive seal self-closing doors with factory tested (over 1,000,000 times) lifetime guaranteed door hinges and torsion type closure system.
- Extruded, aluminum door frames on glass doors.
- Fluorescent interior lighting; integrated door light (IDL) standard on glass & combination door models.
- Incandescent interior lighting standard on solid door models.
- Foamed-in-place polyurethane high density cell insulation (CFC free).
- 4" diameter swivel castors standard equipment. 6" legs available.
- Self-contained system.

### Bottom Mounted Units Have...

- A "no-stoop", lower shelf.
- Allows for top storage.
- Compressor performs in the coolest, most grease-free area of kitchen for ease of compressor load.
- Compressor can be serviced easily, and accessed by a single repairman.

Remote cabinets available 14% off list (condensing units supplied by others; system comes standard with 404A expansion valve and requires R404A refrigerant). Consult factory technical service dept. for BTU information.