

Removable ice machine for easy service



Ice and water dispensers, 115V/60 Hz				
lce storage capacity	Dispense	lce machine cooling	Item number	
90 lb (40.9 kg)	Lever	air	110FB425A-L	
		water	110FB425W-L	
	SensorSAFE	air	110FB425A-S	
		water	110FB425W-S	

Ice-only available, add -I Example: 110FB425A-LI

Ice production				
Temperatures air/water	70/50 F (21/10 C)	90/70 F (32/21 C)		
Air-cooled	425 lb (193.0 kg)	325 lb (147.6 kg)		
Water-cooled	486 lb (220.6 kg)	408 lb (185.2 kg)		
Energy consumption per 100 lb (45.4 kg) ice	N/A	6.0 kWh air-cooled 4.3 kWh water-cooled		
Condenser water consumption	N/A	0.5 gpm (1.9 Lpm) at 70 F (21 C) water		
Water consumption	12.0 gal (45.4 L) of potable water per 100 lb (45.4 kg) of ice			

Symphony Plus[™] ice and water dispenser

110 FB series freestanding with Chewblet® ice machine

Features

90 lb (40.9 kg) ice storage capacity

Removable air- or water-cooled ice machine with up to 425 lb (193.0 kg) daily ice production

- soft, chewable, compressed nugget ice is preferred over cubes¹ and is ideal for patient care
- Quiet Night[™] sleep mode turns off ice machine when idle

Designed with sanitation in mind

- automatic self-flushing of ice machine removes impurities
- drain cup provides internal air gap for added protection of food zone components from drain line contaminants
- Agion[®] silver-based antimicrobial provides protection of key ice and water contact components²
- one-hand lever or SensorSAFE[™] infrared ice dispense

Dependable design, easy to service and clean

- cleaning and sanitizing of entire machine takes only 1 hour
- LED control board provides at-a-glance machine status
- panels are easily removed for accessibility to all components
- ice machine parts are common across all Symphony Plus dispensers
- stainless steel evaporator and auger deliver long life
- Environmentally responsible
 - meets Consortium for Energy Efficiency Tier 2 specifications
 - R404a refrigerant has zero ozone depletion potential
 - ice-only dispensers are ENERGY STAR® certified³
 - continuous ice making process uses less electricity and water

Durable, attractive dispenser

- frame and exterior cabinet are stainless steel with accent trim
- poly drain pan, grille and dispenser lid are corrosion-resistant
- secured top lid

Easy installation and industry's best warranty

- comes fully assembled and installs with three easy connections electric, water and drain
- warranty 3 years parts and labor, 5 years compressor parts

Accessories

- Chilled water option (item# 01063205)
- Pressurized water sanitizing kits (refer to form# 6830)
- Cleaning and sanitizing starter kit (item# 01098789)
- SafeCLEAN[™] ice machine cleaner (item# 00132001)
- Nu-Calgon[®] IMS-III sanitizer, 16 oz bottle (item# 00979674)
- Additional filters (refer to form# 6380, 9905, 6070)
- Additional Symphony Plus accessories (refer to price list)

801 Church Lane | Easton, PA 18040, USA 1.800.523.9361 | 1.610.252.7301 | follettice.com



Innovative solutions, inspired by ice

Specification

Specification		
Ice storage capacity	90 lb (40.9 kg)	
W1 Width, top	25.00" (63.5 cm)	
W2 Width, bottom	26.25" (66.7 cm)	
D1 Depth, top	28.25" (71.8 cm)	
D2 Depth, drain pan	7.00" (17.8 cm)	
D3 Depth, bottom	29.44" (74.8 cm)	
H1 Height	68.12" (173.0 cm)	
H2 Dispense height clearance	7.75" (19.68 cm)	
Ventilation clearance	air-cooled models only – 4.00" (10.16 cm) rear	
Service clearance	12.00" (30.5 cm) top	
C1 115 V/60/1 electrical	11 amps, 0.8 kW 7' (2.1 m) cord, NEMA 5-15 90° hospital-grade plug	
C2 Potable water inlet, ice machine and dispenser	3/8" FPT	
C3 Drain, dispenser	3/4" MPT	
Water-cooled ice machine connections		
C4 condenser inlet C5 condenser drain	3/8" FPT 3/8" FPT	
C6 Ice machine drain	3/4" MPT	
Air temperature	50 -100 F (10 - 38 C)	
Water temperature	45 - 90 F (7 - 32 C)	
Potable water pressure	10 - 70 psi (69 - 483 kpa)	
Condenser water pressure	10 - 125 psi (69-861 kpa)	
Heat rejection	air-cooled models – 5000 BTU/hr water-cooled models – 1400 BTU/hr to air, 3600 BTU/hr to water	
Water flow requirement for water- cooled models	0.25 gpm at 50 F (10 C) 0.5 gpm at 70 F (21 C) 1.25 gpm at 90 F (32 C)	
Approximate ship weight	290 lb (131.5 kg)	
NOTE: For indoor use only		

SHORT FORM SPECIFICATION: (Choose one) ____ Ice and water or ____ ice-only dispenser to be Follett® automatic load in freestanding configuration, with 90 lb (40.9 kg) of storage, water station and (choose one) ____ air- or ____ water-cooled ice machine in base. Dispenser frame and cabinet stainless steel with plastic trim. Environmentally responsible R404a ice machine mounted in base and to be removable as one unit for cleaning and maintenance. Ice machine to produce approximately 425 lb (193.0 kg) per day of Chewblet compressed nugget ice at air temp. of 70 F (21 C), water temp. of 50 F (10 C). Ice machine equipped with automatic self-flushing and Quiet Night sleep mode. Dispenser to have automatic bin level control to start and stop ice machine and separate circuitry to allow dispensing to continue with ice machine removed. Dispenser equipped with 6.00" (15.24 cm) adjustable legs, flanged feet and lightweight plastic top that allows full access to the ice storage area for manual loading of back-up ice. Storage area insulated with non-CFC, high density, foamed-in-place polyurethane. 7' (2.1 m) cord and NEMA 5-15 90° hospital-grade plug provided. NSF and ETL listed.

110 FB series freestanding





air exhaust D2 H2 H1 air intake D3 W2 C1 11 access panel C3 \bigcirc 12.28" (31.2 cm) C2 4.69" 6 (11.91 cm) 33.78" (85.8 cm) 3.69" — (9.37 cm) 31.47" (79.9 cm) 2 69" (6.83 cm) oC4 C5 **▲**14.06" (35.7 åC6 12.38 (31.4 cm) 9.59" (24.35 cm)

Dimensional drawing

D1 [^]

W1

4.50" (11.43 cm)

1 Independent third party studies. Contact Follett for details.

Disclaimer: Antimicrobial protection is limited to the treated components and does not treat water or ice.
ENERGY STAR certification applies only to ice-only dispensers. While the Symphony Plus ice and water dispensers have the same efficient ice makers and refrigeration systems with the same ice machine electrical and water consumption as their complementary ice-only models, there is no ENERGY STAR category for ice and water dispensers at this time.
Aqion is a registered trademark of Sciessent LLC.

ENERGY STAR and the ENERGY STAR mark are registered trademarks owned by the U.S. Environmental Protection Agency.

Calgon is a licensed tradename distributed by Nu-Calgon, in the United States.

Symphony Plus, SensorSAFE, SafeCLEAN and Quiet Night are trademarks of Follett LLC. Chewblet and Follett are registered trademarks of Follett LLC, registered in the US.

Follett reserves the right to change specifications at any time without obligation. Certifications may vary depending on country of origin.

801 Church Lane | Easton, PA 18040, USA 1.800.523.9361 | 1.610.252.7301 | follettice.com

