



# FZR4P ADA-Compatible Performance Plus

medical-grade undercounter freezer

## Features

### Superior temperature performance

- custom-designed microprocessor temperature controller
- air-cooled refrigeration system with heavy duty 1/4 horsepower compressor
- environmentally friendly, non-CFC R404a refrigerant
- programmed automatic defrost every 6 hours
- cabinet-wide temperature remains within +/- 1 C (1.8 F), even with frequent door openings

### Convenience and security

- fits below 34.00" (86.4 cm) ADA countertops without casters
- refrigeration system settings accessed through door-mounted controls
- exterior LED digital temperature display available in user-programmable C or F with choice of product or air temperature
- user-programmable audible and visual high/low alarms
- mechanical lock – mounted on side of door
- lockable controller so set points cannot be inadvertently changed
- dry (NO and NC) contacts for connection to remote alarm systems
- flexible internal storage configuration (drawers and shelves interchangeable)
- Agion® antimicrobial and UV product protection added to molded plastic façade<sup>1</sup>

### Durability and serviceability

- stainless steel construction on exterior and interior
- two epoxy-coated wire shelves standard
- back wall evaporator and front ventilation (no top, back or side clearance required)
- heavy-duty edge-mount self-closing hinges
- field-reversible solid stainless steel door
- integral handle and magnetic gasket door closure

### Warranty

- 2 year parts and labor on refrigeration system
- 5 year parts on compressor

Undercounter freezers			
Controls	Keypad	V/Hz/Ph	Item number
LED	No	115/60/1	FZR4P-00-00
	Yes	115/60/1	FZR4P-KP-00

## Options and accessories

- Keypad and electronic lock
- Extra shelf (item# 01059484)
- Drawer kit (item# 01053644)
- External digital data logger (item# 01057561)
- Replacement probe for digital data logger (item# 01057595)
- Temperature surveillance module (chart recorder) (item# 00168674)
- Replacement charts for temperature surveillance module (item# 00162099)
- Replacement pens for temperature surveillance module (item# 00162081)
- Universal automated medication dispensing system bracket (item# 01059096)
- Glycerine (16 oz) (item# 00959296)
- Stacking kit (item# 01054006)
- Temperature alarm (item# 00112185)
- 17.00" (43.2 cm) pedestal kit (item# 01059120)
- Extra key (item# 01059112)
- Casters (set of 4) (item# 01053636)
- Seismic bracket kit (item# 01059104)

Job


Item

## Specification

Nominal capacity	3.9 cu ft (110 L)
<b>W1</b> Width exterior	23.75" (60.3 cm)
<b>D1</b> Depth cabinet	25.62" (65.1 cm)
Depth with façade	27.00" (68.6 cm)
<b>H1</b> Height exterior	31.38" (79.7 cm)
Height with casters	33.88" (86.1 cm)
Width interior	19.75" (50.2 cm)
Depth interior	18.32" (46.5 cm)
Height interior	18.94" (48.1 cm)
Ventilation clearance	0.0" for top, side and back clearance
<b>C1</b> 115 V/60/1 electrical	7.1 run load amps, NEMA 5-15P 90° hospital-grade plug PVC, SJT, 16GA, 7' (2.1 m) cord
Door	solid, foamed stainless 21.50" x 22.51" x 1.63" (54.6 cm x 57.2 cm x 4.0 cm)
Door lock	cylinder lock
Door handle	molded into front façade
Door hinges	edge-mount, self-closing
Door swing	field-reversible
Storage system	(2) 18.10" x 19.10" (46.0 cm x 48.5 cm) epoxy-coated steel shelves
Gasket	magnetic
Temperature display	standard 7 segment LED
<b>C2</b> 3rd party probe access	rear access port
High and low product temperature alarm	audible and visual, user programmable set points in C or F
Factory set point and operating range	preset at -24 C (-11 F) with an adjustable range from -18 C to -37 C (0 F to -35 F)
Probe error alarm	audible and visual — product temperature probes, refrigeration and defrost
Alarm mute	user selectable
Alarm volume	0 -10 adjustable
Min/max temperature log	shows highest and lowest product temperature since last reset occurred
Product simulation bottle	(1) 60 ml
Remote contacts	NO/NC standard, located on back
Refrigerant and charge	R404a refrigerant, 10 oz
Energy consumption	5.8 kWh/day
Max heat rejection	2157 BTU/hr
Approximate ship weight	205 lb (93 kg)

NOTE: For indoor use only

## Dimensional drawing



**SHORT FORM SPECIFICATION:** Performance Plus undercounter freezer fits under 34.00" (86.4 cm) ADA-height counter with 3.9 cubic feet (110 L) of nominal capacity. Includes (2) epoxy-coated wire shelves, adjustable in 1/2" increments. Environmentally responsible R404a forced-air cooled refrigeration system. Top-mounted controls display product or air temperature in user-selectable C or F. Integral high and low temperature alarming. Storage area insulated with CFC-free, high-density polyurethane foam. 7' (2.1 m) power cord with NEMA 5-15P 90° hospital-grade plug. NSF, UL and CUL listed.

<sup>1</sup> Disclaimer: Antimicrobial protection is limited to the plastic façade.

Agion is a registered trademark of Sciessent LLC.

Follett is a registered trademark of Follett Corporation, registered in the US.

Follett reserves the right to change specifications at any time without obligation. Certifications may vary depending on country of origin.

## FZR4P undercounter freezer